

Common User Data

Machine Name:	Xerox AltaLink C8170 (FB:98:72)
IP Address:	10.61.16.61
Machine Serial Number:	EFQ644116
Fax Line1:	
Machine URL:	https://10.61.16.61
Machine Activation Date:	Nov 23, 2023 15:28:48
Black Impressions:	41
Color Impressions:	37
Total Impressions:	78

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	System Administrator name not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	not present
Extended Fax Card:	not present
Fax Card Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	8192 MB
Device Storage Size:	used=3498MB/total=256060MB (SSD)
EPC Memory Size:	1000 MB
Finisher Type:	BR Booklet Maker Finisher
Finisher Punch:	2/4 Hole
Finisher Folder:	C Fold/Z Fold Unit
Multi-feed Detection Kit:	Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	23:46
Xerox Workplace Cloud	Disabled
E-mail Alerts:	Disabled
Service Plan:	PagePack
Billing Impression Mode:	A3 Impressions
Geographic Region:	Western Hemisphere
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated

Smart Proximity Sensor

Wake on Arrival:	Enabled
Sleep on Departure:	Disabled

Software Versions

Device Software:	120.040.103.33810
Patch Version:	None
Network Controller:	120.040.33810
UI Panel Firmware:	003.002.000000
Marking Engine:	034.045.000
Document Feeder:	001.035.000
Finisher:	006.003.000
Fax:	000.000.000
Scanner:	017.022.004
Troy 6:	004.010.00000
Machine Upgrades:	Not Allowed
Last Successful Upgrade:	December 8, 2023 16:25:55

Media Trays

Troy 1:	Plain, White and Letter (8.5 x 11")
Troy 2:	Plain, White and A4 (210 x 297 mm)
Troy 3:	Plain, White and Letter (8.5 x 11")
Troy 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)
Troy 6:	Plain, White and JIS B5 (182 x 257 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows

Mopria Printing Discovery:	Enabled
Mopria Scanning	Enabled
Authentication	Disabled

Physical Connections

Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:a2:1b:0b
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled

Wireless

Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled

Protocols

TCP/IPv4:

IP Address:	Enabled
Subnet Mask:	10.61.16.61
Router/Gateway:	255.255.255.0
Automatic Addressing:	10.61.16.1
DHCP Server:	DHCP
DHCP Lease Expiration:	10.61.13.223
BOOTP Broadcast:	Sat Dec 16 08:54:49 2023
Self Assigned Address State:	Disabled
Self Assigned Address:	Enabled

TCP/IPv6:

Link Local Address:	Enabled
Use Router Supplied Prefix:	fe80:9e93:4eff:fea2:1b0b
Stateless Global Address 1:	Enabled
Stateless Global Address 2:	fd00:0:2:116:9e93:4eff:fea2:1b0b
Manual Address:	=
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway:	fe80:8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):	

DNS Settings:

Requested Host Name:	XR9C934EA21B08
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.15
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:

Bonjour Printer Name:	Xerox AltaLink C8170 (FB:98:72)
-----------------------	---------------------------------

HTTP:

Force Traffic over Secure Connection (H...	Enabled
IPP	Yes
	Enabled

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:

	Enabled
--	---------

Raw IP Printing:

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP

SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Enabled
FTP:	Passive
Web Services on Device:	Enabled

pps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	6,1,2,3,4,5
PostScript	Installed
Level:	3
Version:	3021.101

PCL

Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed

Embedded Fax:

Fax Line1:	not installed
Fax Line2:	

Server Fax: Enabled

Repository Protocol:	FTP
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Email:	Enabled
--------	---------

Scan to Mailbox: Disabled

Storage Capacity (MB):	23489 MB
Storage Used (MB):	1273 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home: Disabled

Scan To: Enabled

Cloud Services:	Disabled
-----------------	----------

Print From: Enabled

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Xerox Secure Access:	Kerberos
----------------------	----------

Audit Log:	Disabled
------------	----------

IP Sec:	Enabled
---------	---------

IP Filtering:	Disabled
---------------	----------

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	66

802.1x: Disabled

Authentication Method:	EAP-MS-CHAPv2
------------------------	---------------

Job Data Removal:

Scheduled:	Disabled
------------	----------

FIPS 140-3: Disabled

TLS:	TLS 1.1 and TLS 1.2
------	---------------------

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control: Enhanced Security