

Common User Data

Machine Name: Xerox Altalink B8245 MFP (4D:5A:42)
IP Address: 10.61.9.125
Machine Serial Number: ZQV624007
Fax Line1: https://10.61.9.125
Machine URL: http://10.61.9.125
Machine Activation Date: Jan 01, 1970 05:30:00
Total Impressions: 4496

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator:
Machine Location:
System Administrator name not set

Machine Hardware

Fax Card:
Extended Fax Card: not present
Fax Card Memory Size: not present
Foreign Interface Card: not present
Device RAM Size: 8192 MB
Device Storage Size: used=3609MB/total=256060MB (SSD)
EPC Memory Size: 1000 MB
Finisher Punch: Offsetting Catch Tray
Finisher Type: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 21:33
Xerox Workplace Cloud: Disabled
E-mail Alerts: Disabled
Billing Impression Mode: Solid
Geographic Region: Western Hemisphere
Startup Config Report: Enabled
GAT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Disabled
File Sharing: Enabled
JBig2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled
Smart Proximity Sensor: Disabled
Wake on Arrival: Enabled
Sleep on Departure: Disabled
Maximize Detection Range: Disabled

Software Versions

Device Software: 120.041.104.05020
Patch Version: None
Network Firmware: 120.041.05020
UI Panel Firmware: 003.003.00000
User Interface: 120.041.05020
Copy Control: 072.001.000
Marking Engine: 120.041.05020
Document Feeder: 023.026.000
Finisher: 000.000.000
Fax: 000.000.000
OS: 120.104.05020
Scanner: 017.022.010
Software Upgrade: 000.0.0
Troy 2: Allowed
Troy 3: Allowed
Troy 4: Allowed

Media Trays

Troy 1: Plain, White and A4 (210 x 297 mm)
Troy 2: Plain, White and Legal (8.5 x 14")
Troy 3: Plain, White and A4 (210 x 297 mm)
Troy 4: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and x=19.69 inches, y=11.73 in.

Connectivity

Mobile Workflows: Xerox Altalink B8245 MFP (4D:5A:42)
Mopria Printing Discovery: 10.61.9.125
Mopria Scanning: ZQV624007
Authentication: https://10.61.9.125
Universal Print: http://10.61.9.125
Universal Print Registration Status: Jan 01, 1970 05:30:00
Physical Connections: 4496
USB Settings:
Printing Timeout: 5 seconds

Protocols

TCP/IPV4: Enabled
IP Address: 10.61.9.125
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.9.1
DHCP: Enabled
DHCID: 10.61.13.223
TUE Mar 5 16:38:33 2024
BROADCAST: Disabled
Self Assigned Address: Disabled
Self Assigned Address Scope: Disabled
Solid: Disabled
A4 Impressions: Western Hemisphere
Link Local Address: fe80::dc71:c7f:fe01:85fa
Use Router Supplied Prefix: fe80::dc71:c7f:fe01:85fa
Storeless Global Address 1: fd09:cccc:aaaa:0:dc71:c7f:fe01:85fa
Manual Address:
DHCIP Address:
DHCIP Addressing:
Default Gateway: fe80::8af:c5d:ff:fe75:e282
DUID (DHCP Unique Identifier):
DNS Settings: Requested Host Name: XRX8681CF958A97
Requested Host Name: Verified Host Name:
Requested Domain Name: Verified Domain Name:
Release DHCP Leases and DNS Registrati...: Disabled
Multicast DNS: Disabled
Primary DNS Server: 10.61.13.20
Alternate DNS Server 1: 10.61.13.20
Alternate DNS Server 2:
DNS Connection Timeout: 5
Append Device Domain: Disabled
Append Parent Domain: Disabled
DNS Domain Search List: XEROXQA.COM
Prefer IPv6 DNS over IPv4: Enabled
Installed Options: PS.

Software Versions

Device Software: 120.041.104.05020
Patch Version: None
Network Firmware: 120.041.05020
UI Panel Firmware: 003.003.00000
User Interface: 120.041.05020
Copy Control: 072.001.000
Marking Engine: 120.041.05020
Document Feeder: 023.026.000
Finisher: 000.000.000
Fax: 000.000.000
OS: 120.104.05020
Scanner: 017.022.010
Software Upgrade: 000.0.0
Troy 2: Allowed
Troy 3: Allowed
Troy 4: Allowed

Media Trays

Troy 1: Plain, White and A4 (210 x 297 mm)
Troy 2: Plain, White and Legal (8.5 x 14")
Troy 3: Plain, White and A4 (210 x 297 mm)
Troy 4: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and x=19.69 inches, y=11.73 in.

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator:
Machine Location:
System Administrator name not set

Machine Hardware

Fax Card:
Extended Fax Card: not present
Fax Card Memory Size: not present
Foreign Interface Card: not present
Device RAM Size: 8192 MB
Device Storage Size: used=3609MB/total=256060MB (SSD)
EPC Memory Size: 1000 MB
Finisher Punch: Offsetting Catch Tray
Finisher Type: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 21:33
Xerox Workplace Cloud: Disabled
E-mail Alerts: Disabled
Billing Impression Mode: Solid
Geographic Region: Western Hemisphere
Startup Config Report: Enabled
GAT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Disabled
File Sharing: Enabled
JBig2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled
Smart Proximity Sensor: Disabled
Wake on Arrival: Enabled
Sleep on Departure: Disabled
Maximize Detection Range: Disabled

Software Versions

Device Software: 120.041.104.05020
Patch Version: None
Network Firmware: 120.041.05020
UI Panel Firmware: 003.003.00000
User Interface: 120.041.05020
Copy Control: 072.001.000
Marking Engine: 120.041.05020
Document Feeder: 023.026.000
Finisher: 000.000.000
Fax: 000.000.000
OS: 120.104.05020
Scanner: 017.022.010
Software Upgrade: 000.0.0
Troy 2: Allowed
Troy 3: Allowed
Troy 4: Allowed

Media Trays

Troy 1: Plain, White and A4 (210 x 297 mm)
Troy 2: Plain, White and Legal (8.5 x 14")
Troy 3: Plain, White and A4 (210 x 297 mm)
Troy 4: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and x=19.69 inches, y=11.73 in.

Accounting

Accounting Mode: Network Accounting

None
Disabled

Security

Authentication Configuration

Machine UI Authentication:

Locally on the Device
Unlocked
Unlocked
Unlocked

Device Website Authentication:

Locally on the Device
Unlocked
Unlocked

Authentication Server:

Retrieve E-mail from LDAP:
Enabled

Kerberos Primary Realm:
Kerberos

Kerberos Alt 1 Realm:
0.0.0:88

Kerberos Alt 1 Address:
0.0.0:88

SMB Alt 1 NT Domain:
0.0.0:443

Smbcard Ctrl Server:
0.0.0:443

Smbcard Ctrl Domain:
Enabled

Smartcard OCS URL:
0.0.0:443

Smartcard Ctrl Domain:
Enabled

Smartcard Ctrl Server:
0.0.0:443

Card Reader Upgrade Policy:
Enabled

Xerox Secure Access:
Secure Access Server:
0.0.0:443

Secure Access Path:
Enabled

IP Sec:
Disabled

IP Filtering:
Disabled

Security Certificates:
Signed

Machine Certificates Installed:
54

Root Certificates Installed:
802.1X:
Disabled

Authentication Method:
EAP-MS-CHAPv2

Job Data Removal:
Disabled

Scheduled Frequency:
Monthly

FIPS 140-3:
Disabled

TLS:
TLS 1.1 and TLS 1.2

TLS Hash:
SHA-1, SHA-256 and above

Trellix Embedded Control:
Enhanced Security

Third Generation Browser:
X3G_3.24.23_2.324.011_01.00.00

Widget Version:
v1.3.17 c8 20140613

Widget Version:
v2.5.02 g9 20220901

Extensible Service Setup

Third Generation Browser:

Widget Version:

Widget Version: