

37655

Common User Data

Machine Name: Xerox VersaLink C620 (FC:36:48)
 IP Address: 10.61.22.134
 Machine Serial Number: 5322980355
 Machine URL: https://10.61.22.134
 Machine Activation Date: Jan 01, 1970 05:30:00
 Black Impressions: 119
 Color Impressions: 154
 Total Impressions: 273

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set
Managed By
 Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used= 3609MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 19:24
 Xerox Workplace Cloud: Disabled
 E-mail Alerts: Disabled
 Service Plan: Neutral
 Geographic Region: unknown
 Startup Config Report: Enabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 120 minutes
 Auto-Off: Disabled

Software Versions

Device Software: 121.026.004.07210
 Patch Version: None
 Network Controller: 121.026.07210
 UI Panel Firmware: 6.2
 User Interface: 121.026.07210
 Marking Engine: 221.160
 Finisher: 000.000.000
 OS: 221.160
 Software Upgrade: 004.013
 ALTB00T Software Upgrade: 004.013

Machine Upgrades

Allowed
 Last Successful Upgrade: March 20, 2024 17:02:49
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing Discovery: Enabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings

Usb Type A Ports: All Enabled
 Printing Timeout: 5 seconds

Wired:

Ethernet MAC Address: 9c:93:4e:fc:36:4b
 Ethernet Speed/Duplex Setting: auto
Wireless:
 Disabled

Wireless MAC Address:

Network Name (SSID):

BSSID:

Security Mode:

Encryption Algorithm:

Status:

Wi-Fi Direct:

Wireless Hardware:

Wi-Fi Protected Setup (WPS) Name:

Connection Method:

Subnet Prefix Address:

Access Point (SSID):

Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint DL...

iBeacon Hardware:

Bluetooth Device Address:

iBeacon IP Address:

Enabled
 Enabled
 Disabled
 Not Registered

Enabled
 Not Installed

Enabled
 Not Installed

Enabled
 Enabled
 Not Installed

Protocols

TCP/IPV4:

IP Address: 10.61.22.134
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.22.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.224
 DHCP Lease Expiration: Wed Mar 27 17:11:48 2024
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPV6:

Link Local Address: Enabled
 fe80::9e93:4eff:fc36:4b
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:122:9e93:4eff:fc36:4b
 Stateless Global Address 2: ::
 Manual Address: Use DHCP as directed by a router
 DHCP Addressing: Enabled
 DHCP Address: fe80::8afc:5dff:fe75:e282
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRXU9c934efc364b
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrat...: Disabled
 Primary DNS Server: 10.61.7.15
 Alternate DNS Server 1: 10.61.13.20
 Alternate DNS Server 2: ::
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: XEROXQA.COM
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink C620 (FC:36:4B)
HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Translation Not Found
 Proxy Server Address: 10.177.8.91:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.22.134:631

SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:
 Port Number: 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled

Raw IP Printing:
 Port Number 1: Enabled
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

NTP:
 Primary Server: 0.0.0.0:123
 Alternate Server: 0.0.0.0:123

SLP:
 Disabled

FTP Client:
 Enabled
 FTP Client Mode: Passive

Web Services on Device:
 Enabled
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled

Web Services
 Digital Certificate Management and Secur...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,6
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 1 Sided
 Default Output Tray: Center Tray
 Default Output Color: Color
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
PostScript
 Level: Installed
 Version: 3
 Image Quality: 3021.101 Enhanced

PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
 Custom Color Tables: Enabled
 Label: Not Installed

Print From:
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security**Authentication Configuration**

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs Pathway: Unlocked
 Printer Pathway: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device

Authentication Server:

Kerberos Primary Realm: Kerberos
 Kerberos Primary Address: 0.0.0.88
 Kerberos Alt 1 Realm: 0.0.0.88
 Kerberos Alt 1 Address: 0.0.0.88
 SMB NT Domain: 0.0.0.443
 SMB Alt 1 NT Domain: 0.0.0.443
 Smartcard Ctrl Server: 0.0.0.443
 Smartcard Ctrl Domain:
 SmartCard OCSP URL:
 Card Reader Upgrade Policy: Enabled
 Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
 Secure Access Path: 0.0.0.443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed
 Root Certificates Installed: 63

802.1x:

Disabled

Job Data Removal:

Scheduled: Disabled
 Scheduled Frequency: Monthly

FIPS 140-3:

Disabled

TLS:

TLS Hash: TLS 1.1 and TLS 1.2
 SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
 Widget Version: v1.3.17 c8 20140613
 Widget Version: v2.5.04 g9 20240123