

Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:6...
 IP Address: 10.61.9.199
 Machine Serial Number: 5334205608
 Fax Line1:
 Machine URL: https://10.61.9.199
 Machine Activation Date: May 23, 2024 13:36:37
 Black Impressions: 81
 Color Impressions: 57
 Total Impressions: 138

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card: not present
 Extended Fax Card: not present
 Fax Card Memory Size: 0 MB
 Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used=3401MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 08:02
 Xerox Workplace Cloud: Disabled
 E-mail Alerts: Disabled
 Service Plan: Neutral
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 iBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
Smart Proximity Sensor
 Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 121.028.004.13700
 Patch Version: None
 Network Controller: 121.028.13700
 UI Panel Firmware: 6.2
 Marking Engine: 221.168
 Document Feeder: 221.168
 Finisher: 000.000.000
 Fax: 000.000.000
 Scanner: 221.168
Machine Upgrades:
 Last Successful Upgrade: Allowed
 May 23, 2024 10:18:18

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")
 Tray 2: Plain, White and Letter (8.5 x 11")
 Tray 3: Plain, White and x=216mm, y=210mm
 Manual Feeder: Plain, White and Letter (8.5 x 11")
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing Discovery: Enabled
 AirPrint / Mopria Scanning Authentication: Enabled
 Disabled

Physical Connections

USB Settings
 Usb Type A Ports: All Enabled
Wired:
 Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 78.8c:77:46:60:59
 auto
 Disabled

Wireless:

Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
 Not Installed
 Wi-Fi Protected Setup (WPS) Name:
 Access Point (SSID):
 Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di... Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPV4:

IP Address: Enabled
 10.61.9.199
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.9.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.224
 DHCP Lease Expiration: Thu May 30 13:40:14 2024
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPV6:

Enabled
 Link Local Address: fe80::708c:77ff:fe46:6059
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:109:7a8c:77ff:fe46:6059
 Stateless Global Address 2: #
 fd00:0:2:109:314a:b3f4:7c69:83c0
 Manual Address: Use DHCP as directed by a router
 DHCP Addressing: DHCP
 DHCP Address: fe80::8afc.5dff:fe75:e282
 Default Gateway:
 DUJD (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77466059
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati... Disabled
 Primary DNS Server: 10.61.7.15
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46:6...

HTTP:

Force Traffic over Secure Connection (H... Enabled
 Yes
 IPP: Enabled

SNMP

SNMP v1/v2: Enabled
 Disabled
 SNMP v3:

LPR/LPD:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA... Disabled
 LDAP Server 1 Validate Server Certificate... Disabled

SMTP

SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Enabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,5,6
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Embedded Fax:	not installed

Fax Line1	
Fax Line2	
Server Fax:	Enabled
Repository Protocol:	FTP
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Enabled

Email:

Enabled

Scan to Mailbox:

Enabled/Displayed

Storage Capacity (MB):	672 MB
Storage Used (MB):	50 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Disabled

Scan To:

Enabled

Cloud Services:	Disabled
-----------------	----------

Print From:

Enabled

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Kerberos

Xerox Secure Access:

Disabled

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	63

802.1x:

Disabled

Job Data Removal:

Scheduled:	Disabled
------------	----------

FIPS 140-3:

Disabled

TLS:

TLS 1.1 and TLS 1.2

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:

Enhanced Security