

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink B625 MFP (AC:17:78)
HTTP:	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Disabled
Proxy Server Address:	0.0.0.0:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.16.10:631
SNMP:	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	Enabled
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP:	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP:	
SMTP Server:	10.61.9.241:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
POP3:	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirmation Request:	Enabled
Incoming E-mail cover sheet:	Enabled
SMTP:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services:	
Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	1 Sided
Default Output Tray:	Center Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
PostScript:	Install-nd
Level:	3
Version:	3021.101
Image Quality:	Enhanced
PCL:	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables:	Enabled
Label:	Not Installed
Embedded Fax:	not installed
Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Confirmation Sheet:	On
Delay Start:	Disabled
Repository Protocol:	FTP
Repository Server:	0.0.0.0:0
Repository Document Path:	
Workflow Scanning:	Enabled
Confirmation Sheet:	Errors Only
Default Repository Protocol:	FTP
Default Repository Server:	0.0.0.0:0
Default Repository Document Path:	
Default Repository Login Credentials:	
Alt1 Repository Protocol:	Device
Alt1 Repository Server:	FTP
Alt1 Repository Document Path:	0.0.0.0:0
Alt1 Repository Login Credentials:	
Workflow Pool Protocol:	Device
Workflow Pool Server:	FTP
Workflow Pool Path:	0.0.0.0:0
Email:	Enabled
Default From Address:	rath:meenas@xeroxqa.com
Confirmation Sheet:	Errors Only
Auto Send to Self:	Disabled
E-mail Security:	Disabled
Scan to Mailbox:	Enabled/Displayed
View Mailboxes by Default:	Enabled
Storage Capacity (MB):	672 MB
Storage Used (MB):	107 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily
Scan to Home:	Disabled
Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled
Scan To:	Enabled
Cloud Services:	Enabled
Print From:	37711
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Enabled

Protocols (cont.)	
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	
FTP Client:	Disabled
FTP Client Mode:	Enabled
Web Services on Device:	Passive
	Enabled
Apps	
Printing	
Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Embedded Fax:	
Fax Line1:	not installed
Fax Line2:	
Server Fax:	
Repository Protocol:	Enabled
Repository Server:	FTP
Repository Document Path:	0.0.0.0:0
Workflow Scanning:	
Enabled:	Enabled
Email:	
Enabled:	Enabled
Scan to Mailbox:	
Storage Capacity (MB):	Enabled/Displayed
Storage Used (MB):	672 MB
Cleanup of Public Folders:	107 MB
Cleanup of Created Folders:	Enabled
Cleanup Time:	Enabled
	Daily
Scan to Home:	
Disabled:	Disabled
Scan To:	
Enabled:	Enabled
Cloud Services:	Enabled
Print From:	
Enabled:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Enabled
Accounting	
Accounting Mode:	None
Network Accounting:	Disabled
Security	
Authentication Configuration	
Machine UI Authentication:	
Locally on the Device:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	
Locally on the Device:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled
Authentication Server:	
Kerberos:	Kerberos
Xerox Secure Access:	Disabled
Audit Log:	
Enabled:	Enabled
IP Sec:	
Disabled:	Disabled
IP Filtering:	
Disabled:	Disabled
Security Certificates	
Machine Certificate:	Signed
Root Certificates Installed:	69
802.1x:	
Disabled:	Disabled
Job Data Removal:	
Scheduled:	Disabled
FIPS 140-3:	
Disabled:	Disabled
TLS:	
TLS 1.1 and TLS 1.2:	TLS 1.1 and TLS 1.2
TLS Hash:	SHA-1, SHA-256 and above
Trellix Embedded Control:	
Enhanced Security:	Enhanced Security