





Protocols (cont.)

**Bonjour:**  
 Bonjour Printer Name: Xerox VersaLink C620 (FC:36:48)

**HTTP:**  
 Enabled: Enabled  
 Port Number: 80  
 Force Traffic over Secure Connection (SSL): Yes  
 Secure HTTP Port Number: 443  
 Proxy Server: Manual  
 Proxy Server Address: 10.1.1.8:91:8080  
 IPP: Enabled  
 Secure IPP Mode: IPP enabled Secure IPPS  
 IPP Network Path: http://10.61.16.78:631

**SNMP:**  
 SNMP v1/v2: Enabled  
 SNMP v3: Disabled

**LPR/LPD:**  
 Enabled: Enabled  
 Port Number: 515  
 PDL Switching: Disabled  
 PDL Banner Override: Disabled

**Raw IP Printing:**  
 Enabled: Enabled  
 Port Number: 9100  
 Bidirectional: Disabled  
 End of Job Timeout: 300  
 PDL Switching: Disabled

**LDAP:**  
 LDAP Server Friendly Name:  
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389  
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389  
 LDAP Server 2 Search Directory Root:  
 LDAP Server 1 Secure Connection (LDAPS): Disabled  
 LDAP Server 1 Validate Server Certificate: Disabled

**SMTP:**  
 SMTP Server: 0.0.0.0:25  
 Connection Encryption (TLS): No Encryption  
 Validate Server Certificate (TLS):  
 Max Message Size (KB): 1024  
 Number of Fragments: 1  
 Total Job Size (KB): 30000  
 Job Splicing Boundary: Page Boundary  
 Credentials for Auto E-mails: None

**POP3:**  
 POP3 Server: 0.0.0.0:110  
 POP3 Secure Connection (TLS): Disabled  
 E-mail Address:  
 Receipt of E-mail via POP3: Disabled  
 Send Confirmation Request: Enabled  
 Incoming E-mail cover sheet: Enabled

**NTP:**  
 Primary Server: 0.0.0.0:123  
 Alternate Server: 0.0.0.0:123

**SLP:**  
 Disabled: Disabled

**FTP Client:**  
 Enabled: Enabled  
 FTP Client Mode: Passive

**Web Services on Device:**  
 Enabled: Enabled  
 WS-Discovery: Enabled  
 WS-Discovery Multicast: Enabled  
 WS-Print: Enabled

**Web Services:**  
 Digital Certificate Management and Security: Enabled  
 Extensible Service Registration: Enabled  
 Job Limits: Enabled  
 Job Management Extension: Enabled  
 Device Configuration: Enabled  
 Session Control: Enabled  
 User Interface Configuration: Enabled  
 EIP Proxy Configuration: Enabled  
 Xerox Secure Access: Disabled  
 EIP SNMP Configuration: Enabled  
 Print Submission: Enabled  
 Mass Storage Access: Enabled  
 Card Reader Access: Enabled  
 Authentication & Accounting Configuration: Enabled  
 Export Audit Log: Enabled  
 Trilix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Disabled  
 Sys/Start Job: Disabled  
 Delete Held Jobs After: 30 Days  
 Error Sheets: Enabled  
 Paper Substitution: Enabled  
 Tray Priority: 120:1:100  
 Default Copies: 1  
 Default Job Type: Normal Print  
 Default Paper Size: 4x6.75 (US Letter, 11.0x17.0 inches)  
 Default Paper Color: White  
 Default 2 Sided Printing: 1 Sided  
 Default Output Tray: Tray 1 (Top)  
 Default Output Color: Color  
 Default Collated Sets: 80000  
 Default Stapling: No Stapling  
 Offsetting Between Jobs: No Offsetting Between Jobs  
 Archival Marking Mode: Off  
 PostScript Level: Level 3  
 Version: 600.110  
 Image Quality: Standard

**PCL**  
 Version: 5  
 Pitch Size: 100%  
 Point Size: 12.00  
 Font Name: Courier  
 Lines Per Page: 60  
 Custom Color Tables Label: Print From

**Print From:**  
 Saved Jobs for Reprint: 1000  
 Print From USB: Enabled  
 Cloud Services: Disabled



