

Common User Data

Machine Name: Xerox VersaLink C620 (6C:CB:6A)
 IP Address: 10.61.16.154
 Machine Serial Number: UMQ000558
 Machine URL: https://10.61.16.154
 Machine Activation Date: Jul 09, 2024 21:15:45
 Black Impressions: 1489
 Color Impressions: 2921
 Total Impressions: 4410

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used=2984MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 17:27
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Geographic Region: unknown
 Startup Config Report: Disabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 120 minutes
 Auto-Off: Disabled

Software Versions

Device Software: 122.026.005.02900
 Patch Version: None
 Network Controller: 122.026.02900
 UI Panel Firmware: 6.2
 User Interface: 122.026.02900
 Marking Engine: 230.319
 Finisher: 000.000.000
 OS: 230.319
 Software Upgrade: 005.009
 ALTB00T Software Upgrade: 005.009
 Tray 2: A15.51_B2.3
 Tray 3: A15.51_B2.3
 Tray 4: A15.51_B2.3
 Tray 5: A15.51_B2.3

Machine Upgrades:

Last Successful Upgrade: February 5, 2025 06:37:45
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and A4 (210 x 297 mm)
 Tray 5: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings

USB Type A Ports: All Enabled
 USB Type B Port: Disabled
 Connection Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: auto

Wireless:

Wireless MAC Address: Disabled
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
 Not Installed

Wi-Fi Protected Setup (WPS) Name:

Connection Method:
 Subnet Prefix Address:
 Access Point (SSID):
 Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di...: Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: Enabled
 10.61.16.154
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.224
 DHCP Lease Expiration: Thu Feb 13 00:35:32 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
 fe80::1057:d3ff:fe6c:cb6a
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:116:1057:d3ff:fe6c:cb6a
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX1257D36CCB6A
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.15
 Alternate DNS Server 1: 10.61.10.6
 Alternate DNS Server 2:
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: XEROXQA.COM
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink C620 (6C.CB:6A)
HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (HTTPS): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Manual
 Proxy Server Address: 10.177.8.91:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.16.154:631
SNMP:
 SNMP v1/v2: Enabled
 SNMP v3: Disabled
LPR/LPD:
 Port Number: Enabled
 PDL Switching: 515
 PDL Banner Override: Disabled
Raw IP Printing:
 Port Number 1: Enabled
 Bidirectional: 9100
 End of Job Timeout: Disabled
 PDL Switching: 300
LDAP:
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root: Translation Not Found
 LDAP Server 1 Secure Connection (LDAPS): Disabled
 LDAP Server 1 Validate Server Certificate: Disabled
SMTP:
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
POP3:
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled
NTP:
 Primary Server: Disabled
 Alternate Server: 0.0.0.0:123
SLP:
 Disabled
FTP Client:
 Enabled
 FTP Client Mode: Passive
Web Services on Device:
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
Web Services:
 Digital Certificate Management and Security: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configuration: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,2,3,4,5,6
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Color
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
PostScript
 Level: Installed
 Version: 3
 Image Quality: 3021.101 Enhanced
PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
Custom Color Tables
 Label: Enabled
 Not Installed
Print From:
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security**Authentication Configuration**

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs Pathway: Unlocked
 Printer Pathway: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device

Authentication Server:

Kerberos: Kerberos
 Kerberos Primary Realm:
 Kerberos Primary Address: 0.0.0.88
 Kerberos Alt 1 Realm:
 Kerberos Alt 1 Address: 0.0.0.88
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 Smartcard Ctrl Server: 0.0.0.443
 Smartcard Ctrl Domain:
 SmartCard OCSP URL:
 Card Reader Upgrade Policy: Enabled
 Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
 Secure Access Path: 0.0.0.443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed
 Root Certificates Installed: 54

802.1x:

Disabled

Job Data Removal:

Scheduled: Disabled
 Scheduled Frequency: Monthly

FIPS 140-3:

Disabled

TLS:

TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
 Widget Version: v1.3.17 c8 20140613
 Widget Version: v2.5.04 g9 20240123