

Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:2...
IP Address: 10.61.12.154
Machine Serial Number: YCQ293082
Fax Line1:
Machine URL: https://10.61.12.154
Machine Activation Date: Jul 18, 2024 17:05:04
Black Impressions: 1330
Color Impressions: 4215
Total Impressions: 5545

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator: System Administrator name not set
Machine Location: machine location not set
Managed By
Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line
Fax Memory Size: 0 MB
Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=3043MB/total=14004MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: Not Installed
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 13:34
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Plan Activated
Geographic Region: unknown
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
File Sharing: Enabled
JBIG2: Lossless
Energy Saver
Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Smart Proximity Sensor
Wake on Arrival: Not Available
Sleep on Departure:

Software Versions

Device Software: 122.028.005.05000
Patch Version: None
Network Controller: 122.028.05000
UI Panel Firmware: 6.2
Marking Engine: 230.320
Document Feeder: 230.320
Finisher: 000.000.000
Fax: 003.021.016
Scanner: 230.320
Machine Upgrades:
Last Successful Upgrade: February 24, 2025 16:12:11

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Manual Feeder: Plain, White and A4 (210 x 297 mm)

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled
Physical Connections
USB Settings
USB Type A Ports: All Enabled
USB Type B Port: Enabled
Wired:
Ethernet MAC Address: 78:8c:77:46:20:25
Ethernet Speed/Duplex Setting: auto
Wireless:
Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status:
Wi-Fi Direct: Enabled
Wireless Hardware: Not Installed
Wi-Fi Protected Setup (WPS) Name:
Access Point (SSID):
Show Password on Device Touch Screen:
NFC: Enabled
iBeacon (Bluetooth®) for AirPrint Di...: Enabled
iBeacon Hardware: Not Installed
Bluetooth Device Address:
iBeacon IP Address:

Protocols

TCP/IPV4:

Enabled
IP Address: 10.61.12.154
Subnet Mask: 255.255.255.0
10.61.12.1
Router/Gateway: DHCP
Automatic Addressing: 10.61.13.224
DHCP Server: Mon Mar 3 16:22:13 2025
DHCP Lease Expiration: Disabled
BOOTP Broadcast: Enabled
Self Assigned Address State:
Self Assigned Address:

TCP/IPV6:

Enabled
Link Local Address: fe80::7a8c:77ff:fe46:2025
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: fd00:0:2:112:7a8c:77ff:fe46:2025
Stateless Global Address 2: ::
Manual Address:
DHCP Addressing: Use DHCP as directed by a router
DHCP Address:
Default Gateway: fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77462025
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati...: Disabled
Primary DNS Server: 10.61.7.15
Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46:2...
HTTP: Enabled
Force Traffic over Secure Connection (H...: Yes
IPP: Enabled

SNMP

SNMP v1/v2: Enabled
SNMP v3: Disabled

LPR/LPD:

Enabled

Raw IP Printing:

Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
LDAP Server 1 Search Directory Root:
LDAP Server 1 Secure Connection (LDA...: Disabled
LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 0.0.0.0:25
Connect Encryption (TLS): No Encryption
Validate Server Certificate (TLS):
SMTP Authentication Type: Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Disabled

Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Repository Protocol:	SMB
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Enabled

Email:

Enabled

Scan to Mailbox:

Storage Capacity (MB):	672 MB
Storage Used (MB):	50 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Disabled

Scan To:

Enabled

Cloud Services:

Disabled

Print From:

Enabled

Enabled

Enabled

Enabled

Disabled

Disabled

Accounting

None

Disabled

Locally on the Device

Unlocked

Unlocked

Unlocked

Unlocked

Locally on the Device

Locally on the Device

Enabled

Enabled

Kerberos

Disabled

Disabled

Enabled

Disabled

Disabled

Signed

54

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Disabled

Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:2...
IP Address: 10.61.12.154
Machine Serial Number: YCQ293082
Fax Line1:
Machine URL: https://10.61.12.154
Machine Activation Date: Jul 18, 2024 17:05:04
Black Impressions: 1328
Color Impressions: 4207
Total Impressions: 5535

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator: System Administrator name not set
Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line
Fax Memory Size: 0 MB
Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=3012MB/total=14004MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: Not Installed
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 13:34
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Plan Activated
Geographic Region: unknown
Startup Config Report: Enabled
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Enabled
File Sharing: Enabled
JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled

Software Versions

Device Software: 122.028.005.05000
Patch Version: None
Network Controller: 122.028.05000
UI Panel Firmware: 6.2
User Interface: 122.028.05000
Marking Engine: 230.320
Copy Controller: 122.028.05000
Document Feeder: 230.320
Finisher: 000.000.000
Fax: 003.021.016
OS: 230.320
Scanner: 230.320
Software Upgrade: 005.010
ALTB00T Software Upgrade: 005.010

Machine Upgrades:

Last Successful Upgrade: February 24, 2025 16:12:11
Scheduled Auto Upgrades: Disabled
Auto Upgrade Start Time: Daily
Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Manual Feeder: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled
Universal Print: Disabled
Universal Print Registration Status: Not Registered

Physical Connections

USB Settings
USB Type A Ports: All Enabled
USB Type B Port: Enabled
Connection Timeout: 5 seconds
Wired: Enabled
Ethernet MAC Address: 78:8c:77:46:20:25
Ethernet Speed/Duplex Setting: auto
Wireless: Disabled

Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status:

Wi-Fi Direct: Enabled
Wireless Hardware: Not Installed

Wi-Fi Protected Setup (WPS) Name:
Connection Method:
Subnet Prefix Address:
Access Point (SSID):
Show Password on Device Touch Screen:

NFC: Enabled
iBeacon (Bluetooth®) for AirPrint Di...: Enabled
iBeacon Hardware: Not Installed
Bluetooth Device Address:
iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: Enabled
10.61.12.154
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.12.1
Automatic Addressing: DHCP
DHCP Server: 10.61.13.224
DHCP Lease Expiration: Mon Mar 3 16:22:13 2025
BOOTP Broadcast: Disabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
fe80::7a8c:77ff:fe46:2025
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: fd00:0:2:112:7a8c:77ff:fe46:2025
Stateless Global Address 2: ::
Manual Address: Use DHCP as directed by a router
DHCP Addressing: Enabled
DHCP Address: fe80::8afc:5dff:fe75:e282
Default Gateway:
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77462025
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati...: Disabled
Primary DNS Server: 10.61.7.15
Alternate DNS Server 1: 10.61.10.6
Alternate DNS Server 2: ::
DNS Connection Timeout: 5
Append Device Domain: Enabled
Append Parent Domains: Disabled
DNS Domain Search List: XEROXQA.COM.
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46:2...
HTTP:
 Port Number: Enabled
 Force Traffic over Secure Connection (H... 80
 Secure HTTP Port Number: Yes
 Proxy Server: 443
 Proxy Server Address: Manual
 IPP: 10.177.8.91:8080
 Secure IPP Mode: Enabled
 IPP Network Path: IPP and Secure IPPS
 http://10.61.12.154:631

SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:
 Port Number: Enabled
 PDL Switching: 515
 PDL Banner Override: Disabled
 Raw IP Printing: Disabled

Raw IP Printing:
 Port Number 1: Enabled
 Bidirectional: 9100
 End of Job Timeout: Disabled
 PDL Switching: 300

LDAP
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA... Disabled
 LDAP Server 1 Validate Server Certificate... Disabled

SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None
 SMTP Authentication Type: Basic Auth with SMTP

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

NTP:
 Primary Server: Disabled
 Alternate Server: 0.0.0.0:123

SLP:
 Disabled

FTP Client:
 Enabled

FTP Client Mode:
 Passive

Web Services on Device:
 Enabled
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled

Web Services
 Copy Submission: Enabled
 Digital Certificate Management and Securi... Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Scan Submission: Enabled
 Scan Workflow Management: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Scan Template Mgmt: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur... Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1.5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Color
 Default Collated Sets: Enabled
 Default Stopping: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
 PostScript: Installed
 Level: 3
 Version: 3021.101
 Image Quality: Enhanced

PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
 Custom Color Tables: Enabled
 Label: Not Installed

Fax:
 Fax Line1: Disabled
 Fax Line2: Disabled

Server Fax:
 Confirmation Sheet: Enabled
 Delay Start: Errors Only
 Repository Protocol: Disabled
 Repository Server: SMB
 Repository Document Path: 0.0.0.0:0

Workflow Scanning:
 Confirmation Sheet: Enabled
 Default Repository Protocol: Off
 Default Repository Server: SMB
 Default Repository Document Path: 0.0.0.0:0
 Default Repository Login Credentials: Device
 Alt1 Repository Protocol: SMB
 Alt1 Repository Server: 0.0.0.0:0
 Alt1 Repository Document Path: Device
 Alt1 Repository Login Credentials: SMB
 Workflow Pool Protocol: 0.0.0.0:0
 Workflow Pool Server:
 Workflow Pool Path:

Email:
 Enabled
 Default From Address:
 Confirmation Sheet: Errors Only
 Auto Send to Self: Disabled
 E-mail Security: Disabled

Scan to Mailbox:
 View Mailboxes by Default: Enabled
 Storage Capacity (MB): 672 MB
 Storage Used (MB): 50 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Daily

Scan to Home:
 Friendly Name:
 Workflow Name: Disabled
 Auto Create Subdir: Disabled
 Append User Name to Path: Disabled
 Auto Create User Name Dir: Disabled

Scan To:
 Cloud Services: Enabled

Print From:
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From MailBox: Disabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm: Kerberos
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm: Kerberos
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain: SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.0:443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed

Root Certificates Installed: 54

802.1x:

Disabled

Job Data Removal:

Scheduled: Disabled

Scheduled Frequency: Monthly

FIPS 140-3:

Disabled

TLS:

TLS Hash: TLS 1.2 and TLS 1.3

Trellix Embedded Control: SHA-1, SHA-256 and above

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00

Widget Version: v1.3.17 c8 20140613

Widget Version: v2.5.04 g9 20240123

