

Configuration Report

Printed at 20 Feb, 2025 10:16

3338 **ox Versalink® C620 Color Printer**

ipccols (cont.)

Bonjour Printer Name: Bonjour
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: Manual
 Proxy Server Address: 10.177.8.91:8080
 IPP and Secure IPPS: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.16.154:631
 SNMP v1/v2: Disabled
 SNMP v3: Disabled
 LPR/LPD: Enabled
 PDL Switching: Disabled
 PDL Banner Override: Disabled
 Raw IP Printing: Enabled
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled
 LDAP Server 1 Friendly Name: LDAP Server 1
 LDAP Server 1 Primary LDAP Address: 0.0.0.389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.389
 LDAP Server 1 Search Directory Root: Disabled
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled
 SMTP Server: 10.61.10.8:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS): 10240
 Max Message Size (KB): 1
 Number of Fragments: 300000
 Total Job Size (KB): Page Boundary
 Job Splitting Boundary: None
 Credentials for Auto E-mails: 10.61.23.93:110
 POP3 Server: Disabled
 POP3 Secure Connection (TLS): Disabled
 E-mail Address: test@its1.3.com
 Receipt of E-mail via POP3: Enabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Disabled
 NTP: 0.0.0.123
 Primary Server: 0.0.0.123
 Alternate Server: 0.0.0.123
 SLP: Disabled
 FTP Client: Disabled
 FTP Client Mode: Passive
 Web Services on Device: Enabled
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 Web Services: Enabled
 Digital Certificate Management and Secur...: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Enabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Printing
 Banner Sheet: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: 1.2,3,4,5,6
 Tray Priority: 1
 Default Copies: Normal Print
 Default Job Type: x=8.50 inches, y=11.00 inches
 Default Paper Size: White
 Default Paper Color: 2 Sided
 Default 2 Sided Printing: Center Tray
 Default Output Tray: Color
 Default Output Color: Enabled
 Default Colored Sets: Not Available
 Default Stopping: No Offset Between Jobs
 Offsetting Between Jobs: Installed
 Postscript Level: 3
 Version: 3021.101
 Image Quality: Enhanced
 PCL Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Courier Font Name: 60
 Lines Per Page: Enabled
 Custom Color Tables: Not Installed
 Label: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

C

