



Common User Data

Machine Name:	Xerox AltaLink C8230 Color MFP (A2.6...
IP Address:	10.61.16.79
Machine Serial Number:	ZRE674017
Fax Line1:	
Machine URL:	https://10.61.16.79
Machine Activation Date:	Mar 20, 2025 18:28:59
Black Impressions:	3576
Color Impressions:	2814
Total Impressions:	6390

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	2e12e12e12
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set

Managed By

Primary MB Server

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Frontend Interface Card:	not present
Device RAM Size:	4096 MB
Device Storage Size:	used=3330MB/total=256060MB (SSD)
EPC Memory Size:	900 MB
Finisher Type:	Offsetting Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	11:45
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Billing Impression Mode:	A3 Impressions
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated

Smart Proximity Sensor

Wake on Arrival:	Enabled
Sleep on Departure:	Disabled

Software Versions

Device Software:	122.038.005.09310
Patch Version:	None
Network Controller:	122.038.09310
UI Panel Firmware:	003.005.00000
Marking Engine:	030.045.000
Document Feeder:	023.026.000
Finisher:	000.000.000
Fax:	000.000.000
Scanner:	017.024.014
Machine Upgrades:	Allowed
Last Successful Upgrade:	April 4, 2025 12:09:22

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Tray 2:	Plain, White and A4 (210 x 297 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and x119.02 inches, y=12.60 in...

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled

Physical Connections

USB Settings

USB Type A Ports	All Enabled
USB Type B Port	Enabled

Wired:

Ethernet MAC Address:	9c:93:4e:a2:6e:e3
Ethernet Speed/Duplex Setting:	auto

Wireless:

Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	

Wi-Fi Direct:

Wireless Hardware:	Enabled
Wi-Fi Protected Setup™ (WPS) Name:	Not Installed

Access Point (SSID):	
Show Password on Device Touch Screen:	

NFC:

iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Enabled
Bluetooth Device Address:	Not Installed
iBeacon IP Address:	

Protocols

TCP/IP v4:

IP Address:	10.61.16.79
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	10.61.13.223
DHCP Lease Expiration:	Wed Apr 16 16:09:44 2025
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IP v6:

Link Local Address:	Disabled
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:

Requested Host Name:	XXR9C934EA26EE3
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:

Bonjour Printer Name:	Xerox AltaLink C8230 Color MFP (A2.6...
HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP	Enabled

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:

Raw IP Printing:	Enabled
------------------	---------

LDAP

LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificat...	Disabled

SMTP

SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
PostScript	Installed
Level:	3
Version:	1021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present

Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Repository Protocol:	SMB
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:	Enabled
---------------------------	---------

Email:	Enabled
---------------	---------

Scan to Mailbox:	Enabled
Storage Capacity (MB):	46924 MB
Storage Used (MB):	2422 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:	Disabled
----------------------	----------

Scan To:	Enabled
-----------------	---------

Cloud Services:	Disabled
-----------------	----------

Print From:	Enabled
--------------------	---------

Saved Jobs for Reprint:	Enabled
-------------------------	---------

Print From USB:	Enabled
-----------------	---------

Print From MailBox:	Disabled
---------------------	----------

Cloud Services:	Disabled
-----------------	----------

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:	Kerberos
-------------------------------	----------

Xerox Secure Access:	Disabled
-----------------------------	----------

Audit Log:	Enabled
-------------------	---------

IP Sec:	Disabled
----------------	----------

IP Filtering:	Disabled
----------------------	----------

Security Certificates	
------------------------------	--

Machine Certificate:	Signed
----------------------	--------

Root Certificates Installed:	56
------------------------------	----

802.1x:	Disabled
----------------	----------

Job Data Removal:	
--------------------------	--

Scheduled:	Disabled
------------	----------

FIPS 140-3:	Disabled
--------------------	----------

TLS:	TLS 1.2 and TLS 1.3
-------------	---------------------

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:	Enhanced Security
----------------------------------	-------------------



Common User Data

Machine Name:	Xerox AltaLink C8230 Color MFP (A2.6...
IP Address:	10.61.16.79
Machine Serial Number:	ZRE674017
Fax Line1:	
Machine URL:	https://10.61.16.79
Machine Activation Date:	Mar 20, 2025 18:28:59
Black Impressions:	3577
Color Impressions:	2815
Total Impressions:	6392

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	2e12e12e12
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	4096 MB
Device Storage Size:	used=3330MB/total=256060MB (SSD)
EPC Memory Size:	900 MB
Finisher Type:	Offsetting Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	11:45
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Billing Impression Mode:	A3 Impressions
Geographic Region:	unknown
Startup Config Report:	Disabled
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files:	Enabled
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	60 minutes
Auto-Off:	Disabled

Smart Proximity Sensor

Wake on Arrival:	Enabled
Sleep on Departure:	Disabled
Maximize Detection Range:	Disabled

Software Versions

Device Software:	122.038.005.09310
Patch Version:	None
Network Controller:	122.038.09310
UI Panel Firmware:	003.005.00000
User Interface:	122.038.09310
Marking Engine:	030.045.000
Copy Controller:	122.038.09310
Document Feeder:	023.026.000
Finisher:	000.000.000
Fax:	000.000.000
OS:	122.005.09100
Scanner:	017.024.014
Software Upgrade:	122.038.09310
Tray 2:	
Tray 3:	
Tray 4:	
Machine Upgrades:	Allowed
Last Successful Upgrade:	April 4, 2025 12:09:22
Scheduled Auto Upgrades:	Enabled
Auto Upgrade Start Time:	Daily
Auto Upgrade Server:	10.61.9.116:21

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Tray 2:	Plain, White and A4 (210 x 297 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and x=19.02 inches, y=12.60 in...

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:a2:6e:e3
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Connection Method:	
Subnet Prefix Address:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IP Address:	10.61.16.79
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	10.61.13.223
DHCP Lease Expiration:	Wed Apr 16 16:09:44 2025
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Disabled
Link Local Address:	
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway	
DUID (DHCP Unique Identifier):	
DNS Settings:	
Requested Host Name:	XXR9C934EA26EE3
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Alternate DNS Server 1:	10.61.10.6
Alternate DNS Server 2:	10.61.7.15
DNS Connection Timeout:	5
Append Device Domain:	Enabled
Append Parent Domains:	Disabled
DNS Domain Search List	XEROXQA.COM
Prefer IPv6 DNS over IPv4:	Enabled

Installed Options

PS:	Installed
-----	-----------

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox AltaLink C8230 Color MFP (A2:6
HTTP:	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...	Yes
Secure HTTP Port Number:	443
Proxy Server:	Disabled
Proxy Server Address:	0.0.0.0:8080
IPP	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.16.79:631
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	Enabled
Port Number 1:	9100
Bi-directional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate:	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	Disabled
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services	
Copy Submission:	Enabled
Digital Certificate Management and Secur...	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Main Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	Offset Between Jobs
PostScript	Installed
Level:	3
Version:	3021.101
Image Quality:	Standard
PCL	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present
Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Confirmation Sheet:	Errors Only
Delay Start:	Disabled
Repository Protocol:	SMB
Repository Server:	0.0.0.0
Repository Document Path:	

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	FTP
Default Repository Document Path:	10.61.23.93:21
Default Repository Login Credentials:	\
Alt1 Repository Protocol:	Device
Alt1 Repository Server:	SMB
Alt1 Repository Document Path:	0.0.0.0
Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	SMB
Workflow Pool Server:	0.0.0.0
Workflow Pool Path:	

Email:

Default From Address:	
Confirmation Sheet:	Errors Only
Auto Send to Self:	Disabled
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	46924 MB
Storage Used (MB):	2422 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
Print From:	Disabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled



Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled
Authentication Server: Kerberos

Kerberos Primary Realm:
Kerberos Primary Address: 0.0.0.88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address: 0.0.0.88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access: Disabled
Secure Access Server: 0.0.0.443
Secure Access Path:

Audit Log: Enabled
IP Sec: Disabled
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 56

802.1x: Disabled

Job Data Removal: Disabled
Scheduled:
Scheduled Frequency:

FIPS 140-3: Disabled
TLS: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5.011_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123

