

Xerox

[illegible]

Xerox

Enabled	5 seconds	Enabled
---------	-----------	---------

Xerox

Xerox

Enabled
Not Installed

Xerox

enabled

Xerox

English

Xerox

10.61.16.207
255.255.255.0
10.61.16.1
DHCP
10.61.13.223
Thu Apr 3 17:13:50 2025
Disabled

Xerox

```
Enabled
fe80::9e93:4eff:fe679
Enabled
fd00:0:2:116:9e93:4eff:fe679
```

Xerox

```

..
Use DHCP as directed by a router
fe80::8a0c:5dff:fe75:e282

```

Xerox

XR89C934EF679
Enabled
Disabled

Xerox

```
10.61.7.15
10.61.10.6
5
::
Enabled
Disabled
XEROXA.COM
```

Xerox

Enabled	Installed
---------	-----------

Xerox

Xerox

Xerox

Xerox

Protocols (cont.)

Bonjour	Bonjour Printer Name:	Parent
HTTP:	Port Number:	80
Force Traffic over Secure Connection (H...	Secure HTTP Port Number:	Yes
Proxy Server:	Proxy Server Address:	Disabled
IPP	Secure IPP Mode:	IPP and Secure IPPS
SNMP	IPP Network Path:	http://0.0.0.0:161.0.0.0:161
SNMP v1/v2:	SNMP v1/v2:	Enabled
SNMP v3:	SNMP v3:	Disabled
LPR/LPD:	Port Number:	515
PDL Switching:	PDL Switching:	Disabled
PDL Banner Override:	PDL Banner Override:	Disabled
Row IP Printing:	Port Number:	9100
Bidirectional:	End of Job Timeout:	300
PDL Switching:	PDL Switching:	Disabled
LDAP	LDAP Server 1 Friendly Name:	0.0.0.0:389
LDAP Server 1 LDAP Address:	LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Secure Directory Root:	LDAP Server 1 Secure Directory Root:	0.0.0.0:389
LDAP Server 1 Secure Connection (LDA...	LDAP Server 1 Secure Connection (LDA...	Disabled
SMTP	SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	Validate Server Certificate (TLS):	10240
Max Message Size (KB):	Max Message Size (KB):	1
Number of Fragments:	Number of Fragments:	300000
Job Splitting Boundary:	Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	Credentials for Auto E-mails:	None
POP3	POP3 Server:	0.0.0.0:110
E-mail Address:	E-mail Address:	Disabled
POP3 Secure Connection (TLS):	POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	POP3 Validate Server Certificate:	Disabled
Receipt of E-mail via POP3:	Receipt of E-mail via POP3:	Enabled
Send Confirm on Request:	Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Incoming E-mail cover sheet:	Disabled
NTP:	Primary Server:	0.0.0.0:123
Alternate Server:	Alternate Server:	0.0.0.0:123
SLP:	SLP:	Disabled
FTP Client:	FTP Client:	Enabled
Web Services on Device:	Web Services on Device:	Possible
WS-Discovery:	WS-Discovery:	Enabled
WS-Discovery Multicast:	WS-Discovery Multicast:	Enabled
WS-Print:	WS-Print:	Enabled
Web Services	Digital Certificate Management and Secur...	Enabled
Extensible Service Registration:	Extensible Service Registration:	Enabled
Job Limits:	Job Limits:	Enabled
Job Management Extension:	Job Management Extension:	Enabled
Device Configuration:	Device Configuration:	Enabled
Session Data:	Session Data:	Enabled
User Interface Configuration:	User Interface Configuration:	Enabled
EIP Proxy Configuration:	EIP Proxy Configuration:	Disabled
Xerox Secure Access:	Xerox Secure Access:	Enabled
EIP SNMP Configuration:	EIP SNMP Configuration:	Enabled
Print Submission:	Print Submission:	Enabled
Mass Storage Access:	Mass Storage Access:	Enabled
Card Reader Access:	Card Reader Access:	Enabled
Authentication & Accounting Configur...	Authentication & Accounting Configur...	Enabled
Export Audit Log:	Export Audit Log:	Enabled
Trellix Embedded Control:	Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Days(s) 0 Hour(s) 0 Minute(s)	Enabled
Error Sheets:	1, 2, 3, 4, 5	Enabled
Paper Substitution:	Troy Priority:	1
Default Copies:	Default Job Type:	Normal Print
Default Paper Color:	Default Paper Size:	x-210mm, y-297mm
Default 2 Sided Printing:	Default Output Tray:	1 Sided
Default Output Color:	Default Colored Sets:	Black & White
Default Stopping:	Default Stopping:	Not Available
Offsetting Between Jobs:	Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode:	Archival Marking Mode:	Off
PostScript	Level:	Installed
Level:	Level:	3
Version:	Version:	3021.101
Image Quality:	Image Quality:	Enhanced
PCL	Version:	6
Pitch Size:	Pitch Size:	10.00
Font Size:	Font Size:	12.00
Font Name:	Font Name:	Courier
Lines Per Page:	Lines Per Page:	64
Custom Color Tables	Custom Color Tables:	Enabled
Label:	Label:	Not Installed
Saved Jobs for Reprint:	Saved Jobs for Reprint:	Enabled
Print From USB:	Print From USB:	Enabled
Cloud Services:	Cloud Services:	Disabled

Accounting

Accounting Mode:
Network Accounting:

Security

Machine UI Authentication:
Authentication Configuration

Jobs Pathway:
Printer Pathway:
Device Website Authentication:
Authorization:
Authentication Server:

Kerberos Primary Realm:
Kerberos Primary Address:

Kerberos Alt 1 Realm:
Kerberos Alt 1 Address:

SMB NT Domain:
SMB Alt 1 NT Domain:

Smartcard Ctrl Server:
Smartcard Ctrl Domain:

Smartcard OCSP URL:
Card Reader Upgrade Policy:

Card Reader Firmware Version:
Xerox Secure Access:

Secure Access Server:
Secure Access Path:

Audit Log:
IP Sec:

IP Filtering:
Security Certificates

Machine Certificate:
Root Certificates Installed:

802.1x:
Job Data Removal:

Scheduled Frequency:
FIPS 140-3:

TLS:
TLS Hash:

Trellix Embedded Control:
Extensible Service Setup

Third Generation Browser:
Widget Version:

Widget Version:
v1.3.17 c8 20140613

Widget Version:
v2.5.04 g9 20240123

None
Disabled

Locally on the Device
Unlocked
Unlocked
Locally on the Device
Kerberos

0.0.0.0:88
0.0.0.0:88

0.0.0.0:443
0.0.0.0:443

Enabled
Disabled

Enabled
Disabled

Disabled
Signed

54
Disabled

Disabled
Disabled

Enhanced Security
v1.3.17 c8 20140613

X3G_3.24.23.240.5_012_01.00.00
v2.5.04 g9 20240123

