

Protocols (cont.)

**Bonjour:**  
 Bonjour Printer Name: Xerox VersaLink B620 Printer (FE:F6:6A)  
**HTTP:**  
 Port Number: 80  
 Force Traffic over Secure Connection (H...): Yes  
 Secure HTTP Port Number: 443  
 Proxy Server: Manual  
 Proxy Server Address: 10.177.8.91:8080  
 IPP: Enabled  
 Secure IPP Mode: IPP and Secure IPPS  
 IPP Network Path: http://10.61.16.206:631

**SNMP**  
 SNMP v1/v2: Enabled  
 SNMP v3: Disabled

**LPR/LPD:**  
 Port Number: 515  
 PDL Switching: Disabled  
 PDL Banner Override: Disabled

**Raw IP Printing:**  
 Port Number 1: 9100  
 Bidirectional: Disabled  
 End of Job Timeout: 300  
 PDL Switching: Disabled

**LDAP**  
 LDAP Server 1 Friendly Name:  
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389  
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389  
 LDAP Server 1 Search Directory Root:  
 LDAP Server 1 Secure Connection (LDA...): Disabled  
 LDAP Server 1 Validate Server Certificate...: Disabled

**SMTP**  
 SMTP Server: 0.0.0.0:25  
 Connect Encryption (TLS): No Encryption  
 Validate Server Certificate (TLS):  
 Max Message Size (KB): 10240  
 Number of Fragments: 1  
 Total Job Size (KB): 300000  
 Job Splitting Boundary: Page Boundary  
 Credentials for Auto E-mails: None

**POP3**  
 POP3 Server: 0.0.0.0:110  
 POP3 Secure Connection (TLS): Disabled  
 E-mail Address:  
 POP3 Validate Server Certificate:  
 Receipt of E-mail via POP3: Disabled  
 Send Confirm on Request: Enabled  
 Incoming E-mail cover sheet: Enabled

**NTP:**  
 Primary Server: 0.0.0.0:123  
 Alternate Server: 0.0.0.0:123

**SLP:**  
 Disabled

**FTP Client:**  
 Enabled  
 FTP Client Mode: Passive

**Web Services on Device:**  
 Enabled  
 WS-Discovery: Enabled  
 WS-Discovery Multicast: Enabled  
 WS-Print: Enabled

**Web Services**  
 Digital Certificate Management and Securi...: Enabled  
 Extensible Service Registration: Enabled  
 Job Limits: Enabled  
 Job Management Extension: Enabled  
 Device Configuration: Enabled  
 Session Data: Enabled  
 User Interface Configuration: Enabled  
 EIP Proxy Configuration: Enabled  
 Xerox Secure Access: Enabled  
 EIP SNMP Configuration: Enabled  
 Print Submission: Enabled  
 Mass Storage Access: Enabled  
 Card Reader Access: Enabled  
 Authentication & Accounting Configur...: Enabled  
 Export Audit Log: Enabled  
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled  
 Sys/Start Job: Disabled  
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)  
 Error Sheets: Enabled  
 Paper Substitution: Disabled  
 Tray Priority: 1,2,3,5  
 Default Copies: 1  
 Default Job Type: Normal Print  
 Default Paper Size: x=8.50 inches, y=11.00 inches  
 Default Paper Color: White  
 Default 2 Sided Printing: 1 Sided  
 Default Output Tray: Center Tray  
 Default Output Color: Black & White  
 Default Collated Sets: Enabled  
 Default Stapling: Not Available  
 Offsetting Between Jobs: No Offset Between Jobs  
**Archival Marking Mode**: Off  
**PostScript**: Installed  
 Level: 3  
 Version: 3021.101  
 Image Quality: Enhanced

**PCL**  
 Version: 6  
 Pitch Size: 10.00  
 Point Size: 12.00  
 Font Name: Courier  
 Lines Per Page: 60

**Custom Color Tables**: Enabled  
 Label: Not Installed

**Print From:**  
 Saved Jobs for Reprint: Enabled  
 Print From USB: Enabled  
 Cloud Services: Disabled