

37505

Xerox® VersaLink® C415 Color MFP

Configuration Report

Printed at 25 Apr, 2025 08:11



Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:6...
 Address: 10.61.16.35
 Machine Serial Number: S334205608
 Line 1:
 Machine URL: https://10.61.16.35
 Machine Activation Date: Apr 24, 2025 11:58:44
 Total Impressions: 3661
 Machine Impressions: 3008
 Total Impressions: 6669

Machine Profile

Asset Tag:
 Former Asset Tag:
 Service Phone Number:
 Former Support Number:
 Sales Phone Number:
 System Administrator:
 Machine Location: Not set
 Machine Location: machine location not set
 Managed By:
 Primary MB Server:

Machine Hardware

Hard Drive: Not Present
 Memory Size: 0 MB
 Network Interface Card: not present
 Free RAM Size: 1984 MB
 Free Storage Size: used - 3307MB/total - 0MB (eMMC)
 Memory Size: 187 MB
 Activity Kit: Not Installed
 Paper Type: Simple Catch Tray
 Paper Punch: None
 Paper Folder: not present
 Paper Feed Detection Kit: Not Installed

General Setup

Network Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 16:55
 Workplace Cloud: Enabled
 Email Alerts: Disabled
 Security Plan: Metered
 Geographic Region: unknown
 Time Offset: 00:00
 File Sharing: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 File Sharing: Lossless

Energy Saver

Power Sleep: Enabled
 Energy Saver Mode: Job Activated
 Proximity Sensor: Not Available
 Power on Arrival:
 Power on Departure:

Printer Versions

Software: 122.028.005.11200
 Version: None
 Ink Controller: 122.028.11200
 Model Firmware: 6.2
 Imaging Engine: 230.325
 Paper Feeder: 230.325
 Paper: 000.000.000
 Paper: 000.000.000
 Paper: 230.325
 Paper: Not Allowed

Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Tray 3: Plain, White and Letter (8.5 x 11")
 Tray 4: Plain, White and Letter (8.5 x 11")
 Tray 5: Plain, White and Letter (8.5 x 11")
 Tray 6: Plain, White and Letter (8.5 x 11")
 Feeder:
 Tray:

Installed Options

Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 78.8 G77:46:60:59
 auto
 Disabled

Wireless:

Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
 Wi-Fi Protected Setup™ (WPS) Name: Not Installed

Access Point (SSID):
 Show Password on Device Touch Screen:
 NFC:

iBeacon (Bluetooth®) for AirPrint DL...
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: Enabled
 10.61.16.35
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Fri May 2 05:58:44 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
 fe80::7a8c:77ff:fe46:6059
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fe80::7a8c:77ff:fe46:6059
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name:
 Verified Host Name: XRX788C77466059
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrat...: Disabled
 Primary DNS Server: 10.61.7.16
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46:6...

HTTP:

Force Traffic over Secure Connection (H...: Enabled
 IPP: Yes
 Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

Enabled

Raw IP Printing:

Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389

LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption

Validate Server Certificate (TLS):
 SMTP Authentication Type: Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Enabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5,6
Archival Marking Mode:	Off
PostScript:	Installed
Level:	3
Version:	3021.101
PCL:	
Version:	6
Font Name:	Courier
Custom Color Tables:	Enabled
Label:	Not Installed
Fax:	Not Present

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0:0

Workflow Scanning:

	Enabled
--	---------

Email:

	Enabled
--	---------

Scan to Mailbox:

Storage Capacity (MB):	Enabled
Storage Used (MB):	672 MB
Cleanup of Public Folders:	97 MB
Cleanup of Created Folders:	Enabled
Cleanup Time:	Enabled
	Daily

Scan to Home:

	Disabled
--	----------

Scan To:

	Enabled
--	---------

Cloud Services:	Disabled
-----------------	----------

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled
	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

	Kerberos
--	----------

Xerox Secure Access:

	Disabled
--	----------

Audit Log:

	Enabled
--	---------

IP Sec:

	Disabled
--	----------

IP Filtering:

	Disabled
--	----------

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	54

802.1x:

	Disabled
--	----------

Job Data Removal:

Scheduled:	Disabled
------------	----------

FIPS 140-3:

	Disabled
--	----------

TLS:

TLS Hash:	TLS 1.2 and TLS 1.3
	SHA-1, SHA-256 and above

Trellix Embedded Control:

	Enhanced Security
--	-------------------