

Common User Data

Machine Name: ALTA LINK C8230 COLOR MFP A2.6
 IPv4 Address: 10.61.16.79
 Machine Serial Number: ZRE674017
 Fax Line 1: 3338
 Machine URL: https://10.61.16.79
 Machine Activation Date: Mar 20, 2025 18:28:59
 Black Impressions: 3770
 Color Impressions: 3081
 Total Impressions: 6851

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Month Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator:
 Machine Location:

Managed By

Primary MB Server:

Machine Hardware

Fax Card: USB, 1 Line
 Fax Memory Size: 1933 MB
 Foreign Interface Card: not present
 Device RAM Size: 4096 MB
 Device Storage Size: used=3297MB/total=0MB (SSD)
 EPC Memory Size: 900 MB
 Finisher Type: Offsetting Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 11:45
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Billing Impression Mode: A3 Impressions
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 iBIG2: Lossless

Energy Saver

Deep Sleep: Disabled
 Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Enabled
 Sleep on Departure: Disabled

Software Versions

Device Software: 122.038.005.13400
 Patch Version: None
 Network Controller: 122.038.13400
 UI Panel Firmware: 003.005.00000
 Marking Engine: 030.045.000
 Document Feeder: 023.026.000
 Finisher: 000.000.000
 Fax: 003.021.020
 Scanner: 017.024.014
 Machine Upgrades: Allowed
 Last Successful Upgrade: May 19, 2025 17:41:41

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Glossy Cardstock Reloaded, White and A3
 Tray 3: Letterhead, White and B5 (176 x 250 mm)
 Tray 4: Glossy Cardstock, White and Letter (8.5 x ...
 Bypass Tray: Plain, White and x=19.02 inches, y=12.60 in...

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled

Wired:

Ethernet MAC Address: 9c93:4ea2:6ee3
 Ethernet Speed/Duplex Setting: auto

Wireless:

Wireless MAC Address:
 Network Name (SSID): Disabled
 BSSID:

Security Mode:

Enterprise/Regular Client

Status:

Wi-Fi Direct: Enabled

Wireless Hardware: Intel 802.11ac

Wi-Fi Protected Setup™ (WPS) Name:

Access Point (SSID):

Show Password on Device Touch Screen:

NFC: Enabled

iBeacon (Bluetooth®) for AirPrint Di...: Enabled

iBeacon Hardware: Not installed

Bluetooth Device Address:

iBeacon IP Address:

Protocols

TCP/IPv4:

IPv4 Address: 10.61.16.79
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Tue May 27 11:43:03 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
 fe80::9e93:4eff:fea2:6ee3
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address: fd00:0:2:116:f5dd:8c00:7251:da22
 Default Gateway: fe80::8af::5dff:fe75:e282
 DUID (DHCP Unique Identifier): 000100012fbddc19c934ea26ee3

DNS Settings:

Requested Host Name: XRX9C934EA26EE3
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.16
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox AltaLink C8230 Color MFP (A2.6...)

HTTP:

Force Traffic over Secure Connection (H...): Enabled
 HTTP: Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

LPR/LPD: Enabled

Raw IP Printing:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389

LDAP Server 1 Search Directory Root:

LDAP Server 1 Secure Connection (LDA...): Disabled

LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 10.61.23.93:25

Connect Encryption (TLS): No Encryption

Validate Server Certificate (TLS):

SMTP Authentication Type: Basic Auth with SMTP



Protocols (cont.)

POP3
 POP3 Secure Connection (TLS): Disabled
 POP3 Validate Server Certificate:
 E-mail Address:
 NTP: Disabled
 FTP Client: Enabled
 FTP Client Mode: Passive
 Web Services on Device: Enabled

Apps

Printing

Banner Sheet: Disabled
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,2,3,4,5
 PostScript: Installed

PCL
 Version: 6

Font Name: Courier
 Custom Color Tables: Enabled
 Label: Not Installed

Fax: Enabled/Displayed
 Fax Line1: 3338
 Fax Line2:

Server Fax: Enabled
 Repository Protocol: SMB
 Repository Server: 10.61.23.93:445
 Repository Document Path:

Workflow Scanning: Enabled

Email: Enabled

Scan to Mailbox: Enabled
 Storage Capacity (MB): 46924 MB
 Storage Used (MB): 2417 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Daily

Scan to Home: Disabled

Scan To: Enabled

Cloud Services: Disabled

Print From: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From MailBox: Disabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs: Unlocked
 Device: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device
 Retrieve E-mail from LDAP: Enabled

Authentication Server: Kerberos

Xerox Secure Access: Disabled

Audit Log: Enabled

IP Sec: Disabled

IP Filtering: Disabled

Security Certificates
 Machine Certificate: Signed
 Root Certificates Installed: 55

802.1x: Disabled

Job Data Removal:
 Scheduled: Disabled

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3
 TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security

Common User Data

Machine Profile:
 IPv4 Address: 10.61.16.79
 Machine Serial Number: ZRE674017
 Fax Line1: 3338
 Machine URL: https://10.61.16.79
 Machine Activation Date: Mar 20, 2025 18:28:59
 Black Impressions: 3770
 Color Impressions: 3081
 Total Impressions: 6851

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator:
 Managed By:
 Primary MB Server:

Machine Hardware

Fax Card: USB, 1 Line
 Fax Memory Size: 1933 MB
 Foreign Interface Card: not present
 Device RAM Size: 4096 MB
 Device Storage Size: used=3298MB/total=25600MB (SSD)
 EPC Memory Size: 900 MB
 Finisher Type: Offsetting Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 11:45
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Billing Impression Made: A3 Impressions
 Geographic Region: unknown
 Startup Config Report: Disabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 JBIG2: Lossless
Energy Saver
 Deep Sleep: Disabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 60 minutes
 Auto-Off: Disabled
Smart Proximity Sensor
 Wake on Arrival: Enabled
 Sleep on Departure: Disabled
 Maximize Detection Range: Disabled

Software Versions

Device Software: 122.038.005.13400
 Patch Version: None
 Network Controller: 122.038.13400
 UI Panel Firmware: 003.005.00000
 User Interface: 122.038.13400
 Marking Engine: 030.045.000
 Copy Controller: 122.038.13400
 Document Feeder: 023.026.000
 Finisher: 000.000.000
 Fax: 003.021.020
 OS: 122.005.13300
 Scanner: 017.024.014
 Software Upgrade: 122.038.13400
 Tray 2:
 Tray 3:
 Tray 4:
Machine Upgrades:
 Last Successful Upgrade: May 19, 2025 17:41:41
 Scheduled Auto Upgrades: Enabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 10.61.9.116.21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Glossy Cardstock Reloaded, White and A3
 Tray 3: Letterhead, White and B5 (176 x 250 mm)
 Tray 4: Glossy Cardstock, White and Letter (8.5 x
 Bypass Tray: Plain, White and x=19.02 inches, y=12.60 in.

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled
 Connection Timeout: 5 seconds
Wired:
 Ethernet MAC Address: 9e-91-4a-n2-5a-n3
 Ethernet Speed/Duplex Setting: auto
Wireless:

Wireless MAC Address:
 Wireless Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithms:
 Status:
Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed
 Wi-Fi Protected Setup™ (WPS) Name:
 Connection Method:
 Subnet Prefix Address:
Access Point (SSID):

Show Password on Device Touch Screen
NFC:
 iBeacon (Bluetooth®) for AirPrint Di...
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPv4:

IPv4 Address: Enabled
 10.61.16.79
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Tue May 27 11:43:03 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Disabled
 Self Assigned Address: Enabled

TCP/IPv6:

Link Local Address: Enabled
 fe80-9e93-4eff-fea2-6ee3
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address: fd00:02:116:f5dd:8c00:7251:da22
 Default Gateway: fe80:8afcf3dff:fe75:e282
 DUID (DHCP Unique Identifier): 000100012fbdddc19c934ea26ee3

DNS Settings:

Requested Host Name: XRXC934EA26EE3
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrat...: Disabled
 Primary DNS Server: 10.61.7.16
 Alternate DNS Server 1: 10.61.10.6
 Alternate DNS Server 2: 10.61.7.15
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: 10.61.10.6 10.61.10.6 10.61.10.7
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

P5: Installed

Protocols (cont.)

Bonjour:
 Bonjour: Enabled
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Disabled
 Proxy Server Address: 0.0.0.0:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 [PP Network Path: http://10.61.16.79:631

SNMP:
 SNMP v1/v2: Enabled
 SNMP v3: Disabled
LPR/LPD:
 Port Number: Enabled
 PDL Switching: Disabled
 PDL Banner Override: Enabled
 Raw IP Printing: Disabled
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 200
 PDL Switching: Disabled

LDAP:
 LDAP Server 1 Friendly Name: Enabled
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root: Enabled
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificat...: Disabled

SMTP:
 SMTP Server: 10.61.23.93:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS): 10240
 Max Message Size (KB): 1
 Number of Fragments: 300000
 Total Job Size (KB): Page Boundary
 Job Splitting Boundary: None
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None
 SMTP Authentication Type: Basic Auth with SMTP

POP3:
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address: Disabled
 POP3 Validate Server Certificate: Disabled
 Receipt of E-mail via POP3: Enabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Disabled

NTP:
 Primary Server: 0.0.0.0:123
 Alternate Server: 0.0.0.0:123

SLP:
 SLP: Disabled

FTP Client:
 FTP Client: Enabled
 FTP Client Mode: Passive

Web Services on Device:
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled

Web Services:
 Copy Submission: Enabled
 Digital Certificate Management and Securi...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Scan Submission: Enabled
 Scan Workflow Management: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Scan Template Mgmt: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing:
 Banner Sheet: Disabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,2,3,4,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x 8.50 inches, y 11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Main Tray
 Default Output Color: Color
 Default Collocated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: Disabled
 PostScript: Disabled
 Level: 3
 Version: 3021.101
 Image Quality: Standard

PCL:
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
Custom Color Tables: Enabled
 Label: Not Installed
 Enabled/Displayed: Enabled/Displayed
 3338

Fax:
 Fax Line1: Disabled
 Fax Line2: Disabled

Server Fax: Enabled
 Confirmation Sheet: Errors Only
 Delay Start: Disabled
 Repository Protocol: SMB
 Repository Server: 10.61.23.93:445
 Repository Document Path: /

Workflow Scanning: Enabled
 Confirmation Sheet: On
 Default Repository Protocol: FTP
 Default Repository Server: 10.61.23.93:21
 Default Repository Document Path: \\
 Default Repository Login Credentials: Device
 Alt1 Repository Protocol: SMB
 Alt1 Repository Server: 0.0.0.0:0
 Alt1 Repository Document Path: Device
 Alt1 Repository Login Credentials: SMB
 Workflow Pool Protocol: 0.0.0.0:0
 Workflow Pool Server: 0.0.0.0:0
 Workflow Pool Path: Disabled

Email: Enabled
 Default From Address: test@t1s13.com
 Confirmation Sheet: Errors Only
 Auto Send to Self: Disabled
 E-mail Security: Disabled

Scan to Mailbox: Enabled
 View Mailboxes by Default: Enabled
 Storage Capacity (MB): 46924 MB
 Storage Used (MB): 2417 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Daily

Scan to Home: Disabled
 Friendly Name: Disabled
 Workflow Name: Disabled
 Auto Create Subdir: Disabled
 Append User Name to Path: Disabled
 Auto Create User Name Dir: Disabled

Scan To: Enabled
 Cloud Services: Disabled

Print From: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From MailBox: Disabled
 Cloud Services: Disabled



Accounting

Accounting Mode:
Network Accounting:

Name:
Disabled

Security

Authentication Configuration

Machine UI Authentication:

Home: Locally on the Device
Jobs: Unlocked
Device: Unlocked

Device Website Authentication: Locally on the Device

Authorization:

Retrieve E-mail from LDAP: Locally on the Device
Enabled
Kerberos

Authentication Server:

Kerberos Name: **Relink**

Kerberos Primary Address: 0.0.0.88

Kerberos Alt 1 Realm: 00000000

Kerberos Alt 1 Address: 00000000

SMB NT Domain: 00000000

SMB Alt 1 NT Domain: 00000000

Smartcard Ctrl Server: 00000000

Smartcard Ctrl Domain: 00000000

SmartCard OCSP URL: 00000000

Card Reader Upgrade Policy: Enabled

Card Reader Firmware Version: Disabled

Secure Access Server: 0 0 0 0:443

Secure Access Path: Enabled

Audit Log: Disabled

IP Sec: Disabled

IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed

Root Certificates Installed: SS

802.1x: Disabled

Job Data Removal:

Scheduled: Disabled

Scheduled Frequency: Disabled

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_011_01.00.00

Widget Version: v1.3.17 c8 20140613

Widget Version: v2.5.04 g9 20240123

Common User Data

Machine Name: Xerox AltaLink C8230 Color MFP (A26)
 IPv4 Address:
 Machine Serial Number: ZRE674017
 Fax Line1: 3338
 Machine URL:
 Machine Activation Date: Mar 20, 2025 18:28:59
 Black Impressions: 3773
 Color Impressions: 3083
 Total Impressions: 6856

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number: 2e12e12e12
 Supplies Phone Number:
 System Administrator:
 Machine Location:

Managed By

Primary MIB Server:

Machine Hardware

Fax Card: USB, 1 Line
 Fax Memory Size: 1933 MB
 Foreign Interface Card: not present
 Device RAM Size: 4096 MB
 Device Storage Size: used=3304MB/total=256060MB (SSD)
 EPC Memory Size: 900 MB
 Finisher Type: Offsetting Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 11:45
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Billing Impression Mode: A3 Impressions
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 iBIG2: Lossless
Energy Saver
 Deep Sleep: Disabled
 Energy Saver Mode: Job Activated
Smart Proximity Sensor
 Wake on Arrival: Enabled
 Sleep on Departure: Disabled

Software Versions

Device Software: 122.038.005.13400
 Patch Version: None
 Network Controller: 122.038.13400
 UI Panel Firmware: 003.005.000000
 Marking Engine: 030.045.000
 Document Feeder: 023.026.000
 Finisher: 000.000.000
 Fax: 003.021.020
 Scanner: 017.024.014
Machine Upgrades:
 Last Successful Upgrade: Allowed
 May 19, 2025 17:41:41

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Glossy Cardstock Reloaded, White and A3
 Tray 3: Letterhead, White and B5 (176 x 250 mm)
 Tray 4: Glossy Cardstock, White and Letter (8.5 x
 Bypass Tray: Plain, White and x=19.02 inches, y=12.60 in

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled
Wired
 Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:a2:6ee3
 auto
Wireless: Disabled

Wireless MAC Address:
 Network Name (SSID):
 BSSID:

Security Mode:
 Authentication Required:

Status:

Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed
 Wi-Fi Protected Setup™ (WPS) Name:
 Access Point (SSID):

Show Password on Device Touch Screen:
NFC: Enabled
 iBeacon (Bluetooth®) for AirPrint Di...: Enabled
 iBeacon Hardware: Not Installed
 Bluetooth Device Address:
 iBeacon IP Address:

Protocols

TCP/IPv4: Disabled
 IPv4 Address:
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server:
 DHCP Lease Expiration:
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6: Enabled
 Link Local Address: fe80-9e93:4eff:fea2:6ee3
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80-8a1c-5dff:fe75:e282
 DUID (DHCP Unique Identifier): 000100012fbdadc19c934ea26ee3

DNS Settings:

Requested Host Name: XRX9C934EA26EE3
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server:
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox AltaLink C8230 Color MFP (A26)

HTTP:

Force Traffic over Secure Connection (H...: Enabled
 IPP: Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

LPR/LPD: Enabled

Raw IP Printing:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 10.61.23.93:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 SMTP Authentication Type: Basic Auth with SMTP

Protocols (cont.)

POP3	Enabled
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Stability System:	Enabled
Tray Priority:	1,2,3,4,5
PostScript:	Installed
Level:	3
Font Name:	Laurier
PCL:	6
Version:	6
Font Name:	Laurier
Custom Color Tables:	Enabled
Label:	Not Installed
Fax:	Enabled/Displayed
Fax Line1:	3338
Fax Line2:	

Server Fax:	Enabled
Repository Protocol:	SMB
Repository Server:	10.61.23.93.445
Repository Document Path:	/

Workflow Scanning:	Enabled
Email:	Enabled

Scan to Mailbox:	Enabled
Storage Capacity (MB):	46924 MB
Storage Used (MB):	2417 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:	Disabled
----------------------	----------

Scan To:	Enabled
-----------------	---------

Cloud Services:	Disabled
-----------------	----------

Print From:	Enabled
--------------------	---------

Saved Jobs for Reprint:	Enabled
-------------------------	---------

Print From USB:	Enabled
-----------------	---------

Print From MailBox:	Disabled
---------------------	----------

Cloud Services:	Disabled
-----------------	----------

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:	Kerberos
-------------------------------	----------

Xerox Secure Access:	Disabled
-----------------------------	----------

Audit Log:	Enabled
-------------------	---------

IP Sec:	Disabled
----------------	----------

IP Filtering:	Disabled
----------------------	----------

Security Certificates

Machine Certificate:	Signed
----------------------	--------

Root Certificates Installed:	55
------------------------------	----

802.1x:	Disabled
----------------	----------

Job Data Removal:

Scheduled:	Disabled
------------	----------

FIPS 140-3:	Disabled
--------------------	----------

TLS:	TLS 1.2 and TLS 1.3
-------------	---------------------

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:	Enhanced Security
----------------------------------	-------------------

Common User Data

Machine Name: Xerox AltaLink C8230 Color MFP (A20)
 IPv4 Address:
 Machine Serial Number: ZRE674017
 Fax Line: 3338
 Machine URL:
 Machine Activation Date: Mar 20, 2025 18:28:59
 Black Impressions: 3773
 Color Impressions: 3083
 Total Impressions: 6856

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 Support Administrator:
 Attachment Location:

Managed By

Primary MFP Server

Machine Hardware

Fax Card: USB, 1 Line
 Fax Memory Size: 1933 MB
 Foreign Interface Card: not present
 Device RAM Size: 4096 MB
 Device Storage Size: used: 3305MB/total: 256060MB (SSD)
 EPC Memory Size: 900 MB
 Finisher Type: Offsetting Catch Tray
 Finisher Pouch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 11:45
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Billing Impression Mode: A3 Impressions
 Geographic Region: unknown
 Startup Config Report: Disabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 IG2: Lossless

Energy Saver

Deep Sleep: Disabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 60 minutes
 Auto-Off: Disabled

Smart Proximity Sensor

Wake on Arrival: Enabled
 Sleep on Departure: Disabled
 Maximize Detection Range: Disabled

Software Versions

Device Software: 122.038.005.13400
 Patch Version: None
 Network Controller: 122.038.13400
 UI Panel Firmware: 003.005.00000
 User Interface: 122.038.13400
 Marking Engine: 030.045.000
 Copy Controller: 122.038.13400
 Document Feeder: 023.026.000
 Finisher: 000.000.000
 Fax: 003.021.020
 OS: 122.005.13300
 Scanner: 017.024.014
 Software Upgrade: 122.038.13400
 Tray 2:
 Tray 3:
 Tray 4:

Machine Upgrades:

Last Successful Upgrade: May 19, 2025 17:41:41
 Scheduled Auto Upgrades: Enabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 10.61.9.116.21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Glossy Cardstock Reloaded, White and A3
 Tray 3: Letterhead, White and B5 (176 x 250 mm)
 Tray 4: Glossy Cardstock, White and Letter (8.5 x
 Bypass Tray: Plain, White and x: 19.02 inches, y: 12.60 in.

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled
 Connection Timeout: 5 seconds
Wired:
 Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: auto
Wireless:
 Wireless MAC Address: Disabled

Wireless Network: 2.4GHz
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:
Wi-Fi Direct
 Wireless Hardware: Enabled
 Wi-Fi Protected Setup™ (WPS) Name: Not Installed
 Connection Method:
 Subnet Prefix Address:
 Access Point (SSID):
 Show Password on Device Touch Screen

NFC
 iBeacon (Bluetooth®) for AirPrint Di: Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPV4: Disabled
 IPv4 Address:
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server:
 DHCP Lease Expiration:
 BOOTP Broadcast:
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPV6: Enabled
 Link Local Address: fe80::9e93:4eff:fea2:6ee3
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address: fd00:0:2:116:f5dd:8c00:7251:da22
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier): 000100012fbddd:19c934ea26ee3

DNS Settings:

Requested Host Name: XRX9C934EA26EE3
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrat: Disabled
 Primary DNS Server:
 Alternate DNS Server 1:
 Alternate DNS Server 2:
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List:
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed



Protocols (cont.)

Bonjour	
Bonjour (Bonjour)	
HTTP	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Disabled
Proxy Server Address:	0.0.0.0:8080
IPP	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://631
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD	
LPR/LPD:	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Overlay:	Disabled
Raw IP Printing	
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Protocol:	300
PDL Switching:	Disabled
LDAP	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate:	Disabled
SMTP	
SMTP Server:	10.61.23.93:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP	
SLP:	Disabled
FTP Client	
FTP Client Mode:	Enabled
FTP Client Mode:	Passive
Web Services on Device	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services	
Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x: 8.50 inches, y: 11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Main Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stopping:	Not Available
Offprinting Between Jobs:	Default Between Jobs
PostScripts:	Disabled
Level:	3
Version:	3021 101
Image Quality:	Standard

PCL

Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables:	Enabled
Label:	Not Installed
Fax:	Enabled/Displayed
Fax Line1:	3338
Fax Line2:	

Server Fax:

Confirmation Sheet:	Enabled
Errors Only:	Errors Only
Delay Start:	Disabled
Repository Protocol:	SMB
Repository Server:	10.61.23.93:445
Repository Document Path:	/

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	FTP
Default Repository Server:	10.61.23.93:21
Default Repository Document Path:	\
Default Repository Login Credentials:	Device
Alt1 Repository Protocol:	SMB
Alt1 Repository Server:	0.0.0.0
Alt1 Repository Document Path:	
Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	SMB
Workflow Pool Server:	0.0.0.0
Workflow Pool Path:	

Email:

Default From Address:	test@tts13.com
Confirmation Sheet:	Errors Only
Auto Send to Self:	Enabled
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	46924 MB
Storage Used (MB):	2417 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
-----------------	---------

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode:
Network Accounting:

Disabled
Disabled

Security**Authentication Configuration****Machine UI Authentication:**

Home: Locally on the Device
Jobs: Unlocked
Device: Unlocked

Device Website Authentication:

Locally on the Device

Authorization:

Locally on the Device

Retrieve E-mail from LDAP:

Enabled

Authentication Server:**Kerberos Primary Realm:**

0.0.0.88

Kerberos Primary Address:**Kerberos Alt 1 Realm:**

0.0.0.44

SMB NT Domain:**SMB Alt 1 NT Domain:**

0.0.0.443

Smartcard Ctrl Server:**Smartcard Ctrl Domain:****SmartCard OCSP URL:****Card Reader Upgrade Policy:**

Enabled

Card Reader Firmware Version:**Xerox Secure Access:**

Disabled

Secure Access Server:

0.0.0.443

Secure Access Path:**Audit Log:**

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates**Machine Certificate:**

Signed

Root Certificates Installed:

55

802.1x:

Disabled

Job Data Removal:**Scheduled:**

Disabled

Scheduled Frequency:**FIPS 140-3:**

Disabled

TLS:

TLS 1.2 and TLS 1.3

TLS Hash:

SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup**Third Generation Browser:**

X3G_3.24.23_2.40.5_011_01.00.00

Widget Version:

v1.3.17 c8 20140613

Widget Version:

v2.5.04 g9 20240123

