

Common User Data

Machine Name:	Xerox VersaLink B415 MFP (08:5E:51)
IPv4 Address:	10.61.16.152
Machine Serial Number:	5330005914
Fax Line1:	
Machine URL:	https://10.61.16.152
Machine Activation Date:	Aug 29, 2024 16:57:00
Total Impressions:	3439

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2831MB/total=0MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	23:12
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Sold
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated

Smart Proximity Sensor

Wake on Arrival:	Not Available
Sleep on Departure:	

Software Versions

Device Software:	122.029.025.20910
Patch Version:	None
Network Controller:	122.029.20910
UI Panel Firmware:	6.3
Marking Engine:	230.333
Document Feeder:	230.333
Finisher:	000.000.000
Fax:	000.000.000
Scanner:	230.333
Machine Upgrades:	Allowed
Last Successful Upgrade:	July 29, 2025 17:18:23

Media Trays

Tray 1:	Plain, White and Letter (8.5 x 11")
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Enabled
Ethernet MAC Address:	e8:4dec:08:5e:51
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.152
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	10.61.13.223
DHCP Lease Expiration:	Fri Aug 8 12:50:17 2025
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Enabled
Link Local Address:	fe80::ea4d:ecff:fe08:5e51
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	fd00:0:2:116:6eb1:8d8c:2854:47d6
Default Gateway:	fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):	00030001e84dec085e51

DNS Settings:

Requested Host Name:	XXRXE84DEC085E51
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:

Bonjour Printer Name:	Xerox VersaLink B415 MFP (08:5E:51)
HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP	Enabled

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP

LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP

SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink B415 MFP (08:5E:51)

HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Disabled
 Proxy Server Address: 0.0.0.0:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.16.152:631

SNMP:
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:
 Port Number: 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled

Raw IP Printing:
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP:
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP:
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None
 SMTP Authentication Type: Basic Auth with SMTP

POP3:
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 POP3 Validate Server Certificate:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

NTP:
 Primary Server: 0.0.0.0:123
 Alternate Server: 0.0.0.0:123

SLP:
 Disabled

FTP Client:
 FTP Client Mode: Enabled
 Passive

Web Services on Device:
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled

Web Services:
 Copy Submission: Enabled
 Digital Certificate Management and Securi...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Scan Submission: Enabled
 Scan Workflow Management: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Scan Template Mgmt: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Black & White
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
 PostScript: Installed
 Level: 3
 Version: 3021.101
 Image Quality: Enhanced

PCL

Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
 Custom Color Tables: Enabled
 Label: Not Installed
 Not Present

Fax:

Fax Line1:

Fax Line2:

Server Fax:

Confirmation Sheet: Enabled
 Delay Start: Errors Only
 Repository Protocol: Disabled
 Repository Server: SMB
 Repository Document Path: 0.0.0.0:0

Workflow Scanning:

Confirmation Sheet: Enabled
 Default Repository Protocol: Errors Only
 Default Repository Server: SMB
 Default Repository Document Path: 0.0.0.0:0
 Default Repository Login Credentials: Device
 Alt1 Repository Protocol: SMB
 Alt1 Repository Server: 0.0.0.0:0
 Alt1 Repository Document Path: Device
 Alt1 Repository Login Credentials: SMB
 Workflow Pool Protocol: 0.0.0.0:0
 Workflow Pool Server:
 Workflow Pool Path:

Email:

Default From Address:
 Confirmation Sheet: Enabled
 Auto Send to Self: Errors Only
 E-mail Security: Disabled

Scan to Mailbox:

View Mailboxes by Default: Enabled
 Storage Capacity (MB): 672 MB
 Storage Used (MB): 50 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Daily

Scan to Home:

Friendly Name:
 Workflow Name:
 Auto Create Subdir: Disabled
 Append User Name to Path: Disabled
 Auto Create User Name Dir: Disabled

Scan To:

Cloud Services: Disabled
 Print From: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From MailBox: Disabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm: Kerberos
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm: 0.0.0.0:88
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.0:443

Audit Log:

IP Sec: Enabled
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 53
802.1x: Disabled

Job Data Removal:

Scheduled: Disabled
Scheduled Frequency:

FIPS 140-3:

TLS: Disabled
TLS Hash: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123