

Common User Data

Machine Name:	Xerox VersaLink C620 (FC:36:4B)
IPv4 Address:	10.61.15.215
Machine Serial Number:	5322980355
Machine URL:	https://10.61.15.215
Machine Activation Date:	Jul 17, 2025 20:31:11
Black Impressions:	7865
Color Impressions:	7795
Total Impressions:	15660

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2879MB/total=0MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	used=93MB/total=0MB (SSD)
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	12:32
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated

Smart Proximity Sensor

Wake on Arrival:	Not Available
Sleep on Departure:	

Software Versions

Device Software:	123.026.005.24410
Patch Version:	None
Network Controller:	123.026.24410
UI Panel Firmware:	6.2
Marking Engine:	237.002
Finisher:	000.000.000
Machine Upgrades:	Allowed
Last Successful Upgrade:	September 8, 2025 07:09:37

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A6 (105 x 148 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:fc:36:4b
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Discovery:	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.15.215
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.15.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Disabled
Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:	
Requested Host Name:	XRX9C934EFC364B
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrations:	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink C620 (FC:36:4B)
HTTP:	Enabled
Force Traffic over Secure Connection (HTTPS):	Yes
IPP:	Enabled

SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDAP SSL):	Disabled
LDAP Server 1 Validate Server Certificate:	Disabled

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	

Protocols (cont.)	
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps	
Printing	
Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1.6
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021 101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label	Not Installed
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting	
Accounting Mode:	None
Network Accounting:	Disabled

Security	
Authentication Configuration	
Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs Pathway:	Unlocked
Printer Pathway:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Authentication Server:	Kerberos
Xerox Secure Access:	Disabled
Audit Log:	Enabled
IP Sec:	Disabled
IP Filtering:	Disabled
Security Certificates	
Machine Certificate:	Signed
Root Certificates Installed:	54
802.1x:	Disabled
Job Data Removal:	
Scheduled:	Disabled
FIPS 140-3:	Disabled
TLS:	TLS 1.2 and TLS 1.3
TLS Hash:	SHA-1, SHA-256 and above
Trellix Embedded Control:	Enhanced Security

Common User Data

Machine Name:	Xerox VersaLink C620 (FC:36:4B)
IPv4 Address:	10.61.15.215
Machine Serial Number:	5322980355
Machine URL:	https://10.61.15.215
Machine Activation Date:	Jul 17, 2025 20:31:11
Black Impressions:	7866
Color Impressions:	7796
Total Impressions:	15662

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2880MB/total=0MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	used=94MB/total=0MB (SSD)
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	12:32
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Geographic Region:	unknown
Startup Config Report:	Enabled
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files:	Enabled
File Sharing	Enabled
JBIG2	Lossless
Energy Saver	
Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	120 minutes
Auto-Off:	Disabled

Software Versions

Device Software:	123.026.005.24410
Patch Version:	None
Network Controller:	123.026.24410
UI Panel Firmware:	6.2
User Interface:	123.026.24410
Marking Engine:	237.002
Finisher:	000.000.000
OS:	237.002
Software Upgrade:	005.016
ALTBOOT Software Upgrade:	005.016
Machine Upgrades:	Allowed
Last Successful Upgrade:	September 8, 2025 07:09:37
Scheduled Auto Upgrades:	Disabled
Auto Upgrade Start Time:	Daily
Auto Upgrade Server:	0.0.0.0:21

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A6 (105 x 148 mm)

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:fc:36:4b
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Connection Method:	
Subnet Prefix Address:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Discovery:	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.15.215
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.15.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Disabled
Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	
DNS Settings:	
Requested Host Name:	XR9C934EFC364B
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registration:	Disabled
Primary DNS Server:	10.61.7.16
Alternate DNS Server 1:	10.61.10.6
Alternate DNS Server 2:	10.61.7.15
DNS Connection Timeout:	5
Append Device Domain:	Enabled
Append Parent Domains:	Disabled
DNS Domain Search List:	XEROXQA.COM.
Prefer IPv6 DNS over IPv4:	Enabled

Installed Options

PS:	Installed
-----	-----------

## Protocols (cont.)

<b>Bonjour:</b>	
Bonjour Printer Name:	Xerox VersaLink C620 (FC:36:4B)
<b>HTTP:</b>	Enabled
Port Number:	80
Force Traffic over Secure Connection (HTTPS):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Manual
Proxy Server Address:	10.177.8.91:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.15.215:631
<b>SNMP:</b>	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
<b>LPR/LPD:</b>	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
<b>Raw IP Printing:</b>	Enabled
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
<b>LDAP:</b>	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDAPS):	Disabled
LDAP Server 1 Validate Server Certificate:	Disabled
<b>SMTP:</b>	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
SMTP Authentication Type:	Basic Auth with SMTP
<b>POP3:</b>	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
<b>NTP:</b>	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
<b>SLP:</b>	Disabled
<b>FTP Client:</b>	Enabled
FTP Client Mode:	Passive
<b>Web Services on Device:</b>	
WS - Discovery:	Enabled
WS - Discovery Multicast:	Enabled
WS - Print:	Enabled
<b>Web Services:</b>	
Digital Certificate Management and Security:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configuration:	Enabled
Export Audit Log:	Enabled
Tiellix Embedded Control:	Enabled

## Apps

## Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1.6
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x = 210mm, y = 297mm
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode:	Off
PostScript:	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced
<b>PCL:</b>	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	64
Custom Color Tables:	Enabled
Label:	Not Installed
<b>Print From:</b>	
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode: None  
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs Pathway: Unlocked  
Printer Pathway: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device  
Kerberos

Authentication Server:

Kerberos Primary Realm:  
Kerberos Primary Address: 0.0.0.0:88  
Kerberos Alt 1 Realm:  
Kerberos Alt 1 Address: 0.0.0.0:88  
SMB NT Domain:  
SMB Alt 1 NT Domain:  
Smartcard Ctrl Server: 0.0.0.0:443  
Smartcard Ctrl Domain:  
SmartCard OCSP URL:  
Card Reader Upgrade Policy: Enabled  
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled  
Secure Access Path: 0.0.0.0:443

Audit Log:

IP Sec: Enabled

IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed  
Root Certificates Installed: 54  
802.1x: Disabled

Job Data Removal:

Scheduled: Disabled  
Scheduled Frequency:

FIPS 140-3:

TLS: Disabled  
TLS Hash: TLS 1.2 and TLS 1.3  
SHA-1, SHA-256 and above  
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G\_3.24.23\_2.40.5\_012\_01.00.00  
Widget Version: v1.3.17 c8 20140613  
Widget Version: v2.5.04 g9 20240123

