

Xerox® VersaLink® B415 MFP

Configuration Report

Printed at 14 Oct, 2025 12:44 AM

xerox™

Common User Data

Machine Name: Xerox VersaLink B415 MFP (DC:B8:44)
IPv4 Address: 10.61.16.69
Machine Serial Number: 5330005345
Fax Line 1:
Machine URL: https://10.61.16.69
Machine Activation Date: Jul 10, 2025 18:17:28
Total Impressions: 9639

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
Recycling Phone Number:
System Administrator:
Machine Location: Not set
Managed By: machine location not set
Primary MFP Server:

Machine Hardware

ax Card: Not Present
ax Memory Size: 0 MB
oreign Interface Card: not present
evice RAM Size: 1984 MB
evice Storage Size: used=2738MB/total=14004MB (eMMC)
PC Memory Size: 187 MB
oductivity Kit: Not Installed
isher Type: Simple Catch Tray
isher Punch: None
isher Folder: not present
lki-feed Detection Kit: Not Installed

General Setup

note Services: Enabled
note Software Download: Enabled
note Services Trans. Time: 22:25
ax Workplace Cloud: Enabled
mail Alerts: Disabled
vice Plan: Neutral
igraphic Region: unknown
T Offset: +05:30
ring Installation: Allowed (Encrypted Files Only)
Sharing: Enabled
i2: Lossless

Energy Saver

ep Sleep: Disabled
ergy Saver Mode: Job Activated
art Proximity Sensor: Not Available
ke on Arrival:
ep on Departure:

Software Versions

e Software: 123.029.005.28100
Version: None
ork Controller: 123.029.28100
nel Firmware: 6.2
ng Engine: 237.004
nent Feeder: 237.004
at: 000.000.000
237.004
ine Upgrades: Allowed
Successful Upgrade: October 13, 2025 19:15:42

Trays

Tray: Plain, White and A4 (210 x 297 mm)
Plain, White and Letter (8.5 x 11")
Plain, White and Letter (8.5 x 11")
Plain, White and Letter (8.5 x 11")
Plain, White and A4 (210 x 297 mm)

Installed Options

Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled

Physical Connections

USB Settings

USB Type A Ports: All Enabled
USB Type B Port: Disabled

Wired:

Ethernet MAC Address: Enabled
Ethernet Speed/Duplex Setting: 78.8c:77:dc:b8:44
auto
Disabled

Wireless:

Wireless MAC Address:

Network Name (SSID):

BSSID:

Security Mode:

Encryption Algorithm:

Status:

Wi-Fi Direct:

Wireless Hardware: Enabled

Wi-Fi Protected Setup™ (WPS) Name: Not Installed

Access Point (SSID):

Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di...

iBeacon Hardware: Disabled

Bluetooth Device Address: Enabled

iBeacon IP Address: Not Installed

Protocols

TCP/IPV4:

IPv4 Address: Enabled
Subnet Mask: 10.61.16.69
Router/Gateway: 255.255.255.0
Automatic Addressing: 10.61.16.1
DHCP Server: DHCP
DHCP Lease Expiration:
BOOTP Broadcast: Disabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPV6:

Link Local Address: Disabled
Use Router Supplied Prefix:
Stateless Global Address 1:
Stateless Global Address 2:
Manual Address:
DHCP Addressing:
DHCP Address:
Default Gateway:
DUID (DHCP Unique Identifier):

DNS Settings:
Requested Host Name: XR788C77DCB844
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS:
Release DHCP Leases and DNS Registrati..
Primary DNS Server:
Prefer IPv6 DNS over IPv4:
Bonjour:
Bonjour Printer Name:

HTTP:

Force Traffic over Secure Connection (H...

IPP

Requested Host Name:

Verified Host Name:

Requested Domain Name:

Verified Domain Name:

Multicast DNS:

Release DHCP Leases and DNS Registrati..

Primary DNS Server:

Prefer IPv6 DNS over IPv4:

Bonjour:

Bonjour Printer Name:

SNMP

SNMP v1/v2:

SNMP v3:

LPR/LPD:

Raw IP Printing:

LDAP

LDAP Server 1 Primary LDAP Address:

LDAP Server 1 Search Directory Root:

LDAP Server 1 Secure Connection (LDA...

LDAP Server 1 Validate Server Certificate...

SMTP

SMTP Server:

Connect Encryption (TLS):

Validate Server Certificate (TLS):

SMTP Authentication Type:

Xerox VersaLink B415 MFP (DC:B8:44)

Enabled

Yes

Enabled

Enabled

Disabled

Enabled

Enabled

0.0.0.0:389

Disabled

Disabled

0.0.0.0:25

No Encryption

Basic Auth with SMTP