

Common User Data

Machine Name:	Xerox VersaLink B415 MFP (DC:B8:44)
IPv4 Address:	10.61.11.235
Machine Serial Number:	5330005345
Fax Line1:	
Machine URL:	https://10.61.11.235
Machine Activation Date:	Jul 10, 2025 18:17:28
Total Impressions:	9161

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2955MB/total=0MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	01:13
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Plan Activated
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	Not Available

Smart Proximity Sensor

Wake on Arrival:	
Sleep on Departure:	

Software Versions

Device Software:	123.029.005.25400
Patch Version:	None
Network Controller:	123.029.25400
UI Panel Firmware:	6.2
Marking Engine:	237.002
Document Feeder:	237.002
Finisher:	000.000.000
Fax:	000.000.000
Scanner:	237.002
Machine Upgrades:	Not Allowed
Last Successful Upgrade:	September 15, 2025 15:55:56

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Disabled
Ethernet MAC Address:	78:8c:77:dc:b8:44
Ethernet Speed/Duplex Setting:	auto
Wireless:	Enabled
Wireless MAC Address:	00:20:00:1d
Network Name (SSID):	Xerox Local SSID
BSSID:	bc:26:c7:9e:82:2e
Security Mode:	WPA2 Personal
Encryption Algorithm:	AUTO
Status:	Connected
Wi-Fi Direct:	Enabled
Wireless Hardware:	Installed
Wi-Fi Protected Setup™ (WPS) Name:	Xerox VersaLink B415 MFP (DC:B8:
Access Point (SSID):	DIRECT-jz-Xerox VersaLink B415 M
Show Password on Device Touch Screen:	Enabled
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Installed
Bluetooth Device Address:	00:20:00:D7:0A:1C
iBeacon IP Address:	10.61.11.235

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.11.235
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.11.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:	Disabled
-----------	----------

Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:	
Requested Host Name:	XRX788C77DCB844

Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:	Xerox VersaLink B415 MFP (DC:B8:44)
Bonjour Printer Name:	Enabled

HTTP:	Yes
Force Traffic over Secure Connection (H...	Enabled
IPP	

SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389

LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Enabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Troy Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed

Fax:

Fax Line1:	Not Present
Fax Line2:	

Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Email:

Scan to Mailbox:

Storage Capacity (MB):	Enabled
Storage Used (MB):	Enabled
Cleanup of Public Folders:	Disabled
Cleanup of Created Folders:	672 MB
Cleanup Time:	50 MB
	Enabled
	Enabled
	Daily

Scan to Home:

Scan To:

Cloud Services:	Disabled
-----------------	----------

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Xerox Secure Access:

Audit Log:

IP Sec:

IP Filtering:

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	54
802.1x:	Disabled

Job Data Removal:

Scheduled:	Disabled
FIPS 140-3:	Disabled

TLS:

TLS Hash:	TLS 1.2 and TLS 1.3
Trellix Embedded Control:	SHA-1, SHA-256 and above

Detailed

Common User Data

Machine Name:	Xerox VersaLink B415 MFP (DC:B8:44)
IPv4 Address:	10.61.11.235
Machine Serial Number:	5330005345
Fax Line1:	
Machine URL:	https://10.61.11.235
Machine Activation Date:	Jul 10, 2025 18:17:28
Total Impressions:	9161

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2955MB/total=0MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	01:13
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Plan Activated
Geographic Region:	unknown
Startup Config Report:	Enabled
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files:	Disabled
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	120 minutes
Auto-Off:	Disabled

Software Versions

Device Software:	123.029.005.25400
Patch Version:	None
Network Controller:	123.029.25400
UI Panel Firmware:	6.2
User Interface:	123.029.25400
Marking Engine:	237.002
Copy Controller:	123.029.25400
Document Feeder:	237.002
Finisher:	000.000.000
Fax:	000.000.000
OS:	237.002
Scanner:	237.002
Software Upgrade:	005.016
ALTBOOT Software Upgrade:	005.016

Machine Upgrades:

Last Successful Upgrade:	September 15, 2025 15:55:56
Scheduled Auto Upgrades:	Disabled
Auto Upgrade Start Time:	Daily
Auto Upgrade Server:	0.0.0.0:21

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered

Physical Connections

USB Settings

USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds

Wired:

Ethernet MAC Address:	78:8c:77:dc:b8:44
Ethernet Speed/Duplex Setting:	auto

Wireless:

Wireless MAC Address:	00:20:00:d7:0a:1d
Network Name (SSID):	Xerox Lab User
BSSID:	bc:26:c7:9e:82:2e
Security Mode:	WPA2 Personal
Encryption Algorithm:	AUTO
Status:	Connected

Wi-Fi Direct:

Wireless Hardware:	Installed
Wi-Fi Protected Setup™ (WPS) Name:	Xerox VersaLink B415 MFP (DC:B8: Push Button Configuration (PBC)
Connection Method:	172.24.68.0/24
Subnet Prefix Address:	DIRECT-jz-Xerox VersaLink B415 M
Access Point (SSID):	Enabled
Show Password on Device Touch Screen:	Enabled

NFC:

iBeacon (Bluetooth®) for AirPrint Di...

iBeacon Hardware:	Installed
Bluetooth Device Address:	00:20:00:D7:0A:1C
iBeacon IP Address:	10.61.11.235

Protocols

TCP/IPv4:

IPv4 Address:	Enabled
Subnet Mask:	10.61.11.235
Router/Gateway:	255.255.255.0
Automatic Addressing:	10.61.11.1
DHCP Server:	DHCP
DHCP Lease Expiration:	

BOOTP Broadcast:

Self Assigned Address State:	Disabled
Self Assigned Address:	Enabled

TCP/IPv6:

Link Local Address:	Disabled
Use Router Supplied Prefix:	Enabled

Stateless Global Address 1:

Stateless Global Address 2:

Manual Address:

DHCP Addressing:

DHCP Address:

Default Gateway:

DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name:	XRX788C77DCB844
Verified Host Name:	

Requested Domain Name:

Verified Domain Name:

Multicast DNS:

Release DHCP Leases and DNS Registrati...	Enabled
Primary DNS Server:	Disabled

Alternate DNS Server 1:

Alternate DNS Server 2:

DNS Connection Timeout:

Append Device Domain:

Append Parent Domains:

DNS Domain Search List:

Prefer IPv6 DNS over IPv4:

	Enabled
--	---------

Installed Options

PS:	Installed
-----	-----------

Protocols (cont.)

Bonjour:

Bonjour Printer Name:	Xerox VersaLink B415 MFP (DC:B8:44)
HTTP:	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Automatic
Proxy Server Address:	0.0.0.0:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.11.235:631

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:

Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled

Raw IP Printing:

Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled

LDAP

LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled

SMTP

SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP

POP3

POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled

NTP:

Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123

SLP:

FTP Client:	Enabled
FTP Client Mode:	Passive

Web Services on Device:

WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled

Web Services

Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode:	Off
PostScript:	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced

PCL

Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables:	Enabled
Label:	Not Installed

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	Errors Only
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0:0

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	0.0.0.0:0
Default Repository Login Credentials:	Device
Alt1 Repository Protocol:	SMB
Alt1 Repository Server:	0.0.0.0:0
Alt1 Repository Document Path:	
Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	SMB
Workflow Pool Server:	0.0.0.0:0
Workflow Pool Path:	

Email:

Default From Address:	
Confirmation Sheet:	Enabled
Auto Send to Self:	Errors Only
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Disabled
Storage Capacity (MB):	Disabled
Storage Used (MB):	Enabled
Cleanup of Public Folders:	672 MB
Cleanup of Created Folders:	50 MB
Cleanup Time:	Enabled

Scan to Home:

Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
-----------------	---------

Print From:

Saved Jobs for Reprint:	Disabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled

*Deleted
Continuation***Accounting**

Accounting Mode: None
Network Accounting: Disabled

Security**Authentication Configuration**

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm: Kerberos
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm: 0.0.0.0:88
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain: 0.0.0.0:443
SMB Alt 1 NT Domain: 0.0.0.0:443
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain: 0.0.0.0:443
SmartCard OCSP URL: 0.0.0.0:443
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version: 0.0.0.0:443

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.0:443

Audit Log:**IP Sec:****IP Filtering:****Security Certificates**

Machine Certificate: Signed
Root Certificates Installed: 54

802.1x:**Job Data Removal:**

Scheduled: Disabled
Scheduled Frequency: Disabled

FIPS 140-3:**TLS:**

TLS Hash: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123