

Common User Data

Machine Name:	Xerox VersaLink B620 Printer (FE:F6:6E)
IPv4 Address:	10.61.16.166
Machine Serial Number:	5320705365
Machine URL:	https://10.61.16.166
Machine Activation Date:	Apr 17, 2023 19:09:32
Total Impressions:	2598

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2739MB/total=14004MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	06:34
Xerox Workplace Cloud	Disabled
E-mail Alerts:	Disabled
Service Plan:	Neutral
Geographic Region:	unknown
Startup Config Report:	Enabled
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files:	Enabled
File Sharing	Enabled
JBIG2	Lossless
Energy Saver	
Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	50 minutes
Auto-Off:	Disabled

Software Versions

Device Software:	123.027.005.27600
Patch Version:	None
Network Controller:	123.027.27600
UI Panel Firmware:	6.2
User Interface:	123.027.27600
Marking Engine:	237.003
Finisher:	000.000.000
OS:	237.003
Software Upgrade:	006.001
ALTB00T Software Upgrade:	006.001
Tray 2:	A16.47_B2.3
Tray 3:	A16.47_B2.3
Tray 4:	A16.47_B2.3
Machine Upgrades:	
Last Successful Upgrade:	Allowed
Scheduled Auto Upgrades:	October 9, 2025 16:15:05
Auto Upgrade Start Time:	Disabled
Auto Upgrade Server:	Daily
	0.0.0.0:21

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Tray 2:	Plain, White and A4 (210 x 297 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:fe:f6:6e
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Connection Method:	
Subnet Prefix Address:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.166
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Enabled
Link Local Address:	fe80::9e93:4eff:fefe:f66e
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	fd00:0:2:116:deaf:f3ffa060:c0b2
Default Gateway:	fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):	000300019c934efef66e
DNS Settings:	
Requested Host Name:	XRX9C934EFEF66E
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Alternate DNS Server 1:	10.61.10.6
Alternate DNS Server 2:	10.61.7.15
DNS Connection Timeout:	5
Append Device Domain:	Enabled
Append Parent Domains:	Disabled
DNS Domain Search List:	XEROXQA.COM.
Prefer IPv6 DNS over IPv4:	Enabled

Installed Options

PS:	Installed
Microsoft Custom Authentication:	Installed

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink B620 Printer (FE:F6:6E)
HTTP:	
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Manual
Proxy Server Address:	10.177.8.91:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.16.166:631
SNMP:	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP:	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP:	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3:	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	
SLP:	Disabled
FTP Client:	
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
Web Services:	
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	2,3,4,5,1
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=210mm, y=297mm
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	Offset Between Jobs
Archival Marking Mode:	Swedish
PostScript:	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced
PCL:	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	64
Custom Color Tables:	Enabled
Label:	Not Installed
Print From:	
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs Pathway: Unlocked
Printer Pathway: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Authentication Server: Kerberos

Kerberos Primary Realm:
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access: Disabled
Secure Access Server: 0.0.0.0:443
Secure Access Path:

Audit Log: Enabled
IP Sec: Disabled
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: S4
802.1x: Disabled

Job Data Removal: Disabled
Scheduled:
Scheduled Frequency:

FIPS 140-3: Disabled
TLS: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123

Common User Data

Machine Name:	Xerox VersaLink B620 Printer (FE:F6:6E)
IPv4 Address:	10.61.16.166
Machine Serial Number:	5320705365
Machine URL:	https://10.61.16.166
Machine Activation Date:	Apr 17, 2023 19:09:32
Total Impressions:	2598

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set

Managed By

Primary MB Server:

Machine Hardware

Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used= 2739MB/total=14004MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	06:34
Xerox Workplace Cloud	Disabled
E-mail Alerts:	Disabled
Service Plan:	Neutral
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless
Energy Saver	
Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	Not Available
Wake on Arrival:	
Sleep on Departure:	

Software Versions

Device Software:	123.027.005.27600
Patch Version:	None
Network Controller:	123.027.27600
UI Panel Firmware:	6.2
Marking Engine:	237.003
Finisher:	000.000.000
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 9, 2025 16:15:05

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Tray 2:	Plain, White and A4 (210 x 297 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Installed Options

PS:	Installed
Microsoft Custom Authentication:	Installed

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mapria Printing:	Enabled

Physical Connections

USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:fe:f6:6e
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled

Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.166
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP

DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:	Enabled
Link Local Address:	fe80::9e93:4eff:fefe:f66e
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	fd00:0:2:116::deaf:f3ff:a060:c0b2
Default Gateway:	fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):	000300019c934efef66e

DNS Settings:	
Requested Host Name:	XRX9C934EFEF66E
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrat...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:

Bonjour Printer Name:	Xerox VersaLink B620 Printer (FE:F6:6E)
-----------------------	---

HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP	Enabled

SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	2,3,4,5,1
Archival Marking Mode	Swedish
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs Pathway:	Unlocked
Printer Pathway:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Authentication Server:	Kerberos
Xerox Secure Access:	Disabled
Audit Log:	Enabled
IP Sec:	Disabled
IP Filtering:	Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	54
802.1x:	Disabled

Job Data Removal:

Scheduled:	Disabled
FIPS 140-3:	Disabled

TLS: TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security