

Xerox® VersaLink® C415 Color MFP

Configuration Report

Printed at 23 Oct, 2025 07:22



Common User Data

Machine Name:	Xerox VersaLink C415 Color MFP (46:6...
IPv4 Address:	10.61.16.76
Machine Serial Number:	5334205420
Line 1:	
Machine URL:	https://10.61.16.76
Machine Activation Date:	Sep 24, 2025 15:07:05
Black Impressions:	1237
Color Impressions:	796
Total Impressions:	2033

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Applies Phone Number:	
Cycling Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By:	
Primary MB Server:	

Machine Hardware

FX Card:	Not Present
FX Memory Size:	0 MB
Foreign Interface Card:	not present
Service RAM Size:	1984 MB
Service Storage Size:	used=3355MB/total=13925MB (eMMC)
FX Memory Size:	187 MB
Productivity Kit:	used=135MB/total=500107MB (HDD)
Catcher Type:	Simple Catch Tray
Catcher Punch:	None
Catcher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	12:47
Xerox Workplace Cloud:	Enabled
Email Alerts:	Disabled
Service Plan:	Plan Activated
Geographic Region:	unknown
MT Offset:	00:00
Printing Installation:	Allowed (Encrypted Files Only)
File Sharing:	Enabled
IG2:	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor:	Not Available

Smart Proximity Sensor

Wake on Arrival:

Sleep on Departure:

Software Versions

Service Software:	123.028.005.28800
Patch Version:	None
Network Controller:	123.028.28800
UI Panel Firmware:	6.2
Marking Engine:	237.004
Document Feeder:	237.004
Catcher:	000.000.000
FX:	000.000.000
Scanner:	237.004

Machine Upgrades:

Last Successful Upgrade: October 17, 2025 11:01:01

Media Trays

Tray 1:	Plain, White and Letter (8.5 x 11")
Manual Feeder:	Plain, White and Letter (8.5 x 11")

Media Trays

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning:	Enabled
Authentication Required:	Disabled

Physical Connections

USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	
Ethernet MAC Address:	Enabled
Ethernet Speed/Duplex Setting:	78.8c:77:46:60:5f
Wireless:	auto
Wireless MAC Address:	Disabled
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	

Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	

NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.76
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:	Enabled
Link Local Address:	
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:	
Requested Host Name:	XRX788C7746605F
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink C415 Color MFP (46:6...
HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP:	Enabled

SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Installed Options

Options:	Installed
----------	-----------

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Enabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0:0

Workflow Scanning:

Enabled

Email:

Enabled

Scan to Mailbox:

Enabled

Storage Capacity (MB):	23071 MB
Storage Used (MB):	1216 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Disabled

Scan To:

Enabled

Cloud Services:	Disabled
-----------------	----------

Print From:

Enabled

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked

Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Kerberos

Xerox Secure Access:

Disabled

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	48

802.1x:

Disabled

Image Overwrite

Immediate:	Installed/Enabled
Scheduled:	Disabled

FIPS 140-3:

Disabled

TLS:

TLS 1.2 and TLS 1.3

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:

Enhanced Security

Xerox® VersaLink® C415 Color MFP

Configuration Report

Printed at 23 Oct, 2025 07:23



Common User Data

Machine Name:	Xerox VersaLink C415 Color MFP (46:6...
Pv4 Address:	10.61.16.76
Machine Serial Number:	5334205420
ax Line1:	
Machine URL:	https://10.61.16.76
Machine Activation Date:	Sep 24, 2025 15:07:05
lack Impressions:	1238
olor Impressions:	797
otal Impressions:	2035

Machine Profile

erox Asset Tag:	
ustomer Asset Tag:	
ervice Phone Number:	
ustomer Support Number:	
upplies Phone Number:	
ecycling Phone Number:	
ystem Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

ax Card:	Not Present
ax Memory Size:	0 MB
oreign Interface Card:	not present
evice RAM Size:	1984 MB
evice Storage Size:	used=3353MB/total=13925MB (eMMC)
PC Memory Size:	187 MB
roductivity Kit:	used=136MB/total=500107MB (HDD)
inisher Type:	Simple Catch Tray
inisher Punch:	None
inisher Folder:	not present
ulti-feed Detection Kit:	Not Installed

General Setup

emote Services:	Enabled
emote Software Download:	Enabled
emote Services Trans. Time:	12:47
erox Workplace Cloud	Enabled
-mail Alerts:	Disabled
ervice Plan:	Plan Activated
eographic Region:	unknown
tartup Config Report:	Enabled
MT Offset:	00:00
loning Installation	Allowed (Encrypted Files Only)
llow Print Submission of Clone Files:	Disabled
ile Sharing	Enabled
BIG2	Lossless
Energy Saver	
Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	120 minutes
Auto-Off:	Disabled

Software Versions

evice Software:	123.028.005.28800
atch Version:	None
etwork Controller:	123.028.28800
II Panel Firmware:	6.2
Iser Interface:	123.028.28800
arking Engine:	237.004
opy Controller:	123.028.28800
ocument Feeder:	237.004
inisher:	000.000.000
ax:	000.000.000
IS:	237.004
canner:	237.004
oftware Upgrade:	006.001
LTBOOT Software Upgrade:	006.001
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 17, 2025 11:01:01
Scheduled Auto Upgrades:	Disabled
Auto Upgrade Start Time:	Daily
Auto Upgrade Server:	0.0.0.0:21

Media Trays

ray 1:	Plain, White and Letter (8.5 x 11")
Manual Feeder:	Plain, White and Letter (8.5 x 11")

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered

Physical Connections

USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds
Wired:	Enabled
Ethernet MAC Address:	78:8c:77:46:60:5f
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled

Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Connection Method:	
Subnet Prefix Address:	
Access Point (SSID):	
Show Password on Device Touch Screen:	

NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.76
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:	Enabled
Link Local Address:	
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:

Requested Host Name:	
Verified Host Name:	XRX788C7746605F
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Alternate DNS Server 1:	10.61.10.6
Alternate DNS Server 2:	10.61.7.15
DNS Connection Timeout:	5
Append Device Domain:	Enabled
Append Parent Domains:	Disabled
DNS Domain Search List:	XEROXQA.COM.
Prefer IPv6 DNS over IPv4:	Enabled

Installed Options

PS:	Installed
-----	-----------

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink C415 Color MFP (46:6...
HTTP:	
Port Number:	Enabled
Force Traffic over Secure Connection (H...	80
Secure HTTP Port Number:	Yes
Proxy Server:	443
Proxy Server Address:	Automatic
IPP	0.0.0.0:8080
Secure IPP Mode:	Enabled
IPP Network Path:	IPP and Secure IPPS
SNMP	
SNMP v1/v2:	http://10.61.16.76:631
SNMP v3:	Enabled
LPR/LPD:	
Port Number:	Disabled
PDL Switching:	515
PDL Banner Override:	Disabled
Raw IP Printing:	
Port Number 1:	Enabled
Bidirectional:	9100
End of Job Timeout:	Disabled
PDL Switching:	300
LDAP	
LDAP Server 1 Friendly Name:	Disabled
LDAP Server 1 Primary LDAP Address:	Disabled
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	0.0.0.0:389
LDAP Server 1 Secure Connection (LDA...	0.0.0.0:389
LDAP Server 1 Validate Server Certificate...	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	
Primary Server:	Enabled
Alternate Server:	0.0.0.0:123
SLP:	
SLP:	0.0.0.0:123
FTP Client:	
FTP Client Mode:	Disabled
Web Services on Device:	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services	
Copy Submission:	Enabled
Digital Certificate Management and Securi...	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1.5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x: 8.50 inches, y: 11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode	
PostScript	Off
Level:	Installed
Version:	3
Image Quality:	3021.101
PCL	
Version:	Enhanced
Pitch Size:	6
Point Size:	10.00
Font Name:	12.00
Lines Per Page:	Courier
Custom Color Tables	
Label:	60
	Enabled
	Not Installed
	Not Present

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	Errors Only
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	0.0.0.0
Default Repository Login Credentials:	Device
Alt1 Repository Protocol:	SMB
Alt1 Repository Server:	0.0.0.0
Alt1 Repository Document Path:	Device
Alt1 Repository Login Credentials:	SMB
Workflow Pool Protocol:	0.0.0.0
Workflow Pool Server:	0.0.0.0
Workflow Pool Path:	

Email:

Default From Address:	Enabled
Confirmation Sheet:	Errors Only
Auto Send to Self:	Disabled
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	Enabled
Storage Used (MB):	23071 MB
Cleanup of Public Folders:	1216 MB
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Friendly Name:	Disabled
Workflow Name:	Disabled
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
-----------------	---------

Print From:

Saved Jobs for Reprint:	Disabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled



Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled
Authentication Server: Kerberos

Kerberos Primary Realm:
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access:
Secure Access Server: Disabled
Secure Access Path: 0.0.0.0:443

Audit Log: Enabled
IP Sec: Disabled
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 48
302.1x: Disabled

Image Overwrite

Immediate: Installed/Enabled
Scheduled: Disabled
Scheduled Frequency:

IPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3
TLS Hash: SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security

Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
Vidget Version: v1.3.17 c8 20140613
Vidget Version: v2.5.04 g9 20240123

