

Common User Data

Machine Name:	Xerox AltaLink B8255 MFP (19:DA:41)
IPv4 Address:	10.61.11.61
Machine Serial Number:	ZQV624012
Fax Line1:	
Machine URL:	https://10.61.11.61
Machine Activation Date:	Jan 01, 2021 05:45:36
Total Impressions:	312

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	+ , *987654321
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	4096 MB
Device Storage Size:	used=3320MB/total=256060MB (SSD)
EPC Memory Size:	900 MB
Finisher Type:	Offsetting Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	21:04
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Billing Impression Mode:	A3 Impressions
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless
Energy Saver	
Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	
Wake on Arrival:	Enabled
Sleep on Departure:	Disabled

Software Versions

Device Software:	123.041.005.28800
Patch Version:	None
Network Controller:	123.041.28800
UI Panel Firmware:	003.005.00000
Marking Engine:	072.002.000
Document Feeder:	023.026.000
Finisher:	000.000.000
Fax:	000.000.000
Scanner:	017.025.003
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 22, 2025 16:26:09

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Tray 2:	Plain, White and A3 (297 x 420 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Disabled
Ethernet MAC Address:	e8:4d:ec:19:da:41
Ethernet Speed/Duplex Setting:	auto
Wireless:	Enabled
Wireless MAC Address:	58:ef:68:27:67:40
Network Name (SSID):	Xerox Lab User
BSSID:	bc:26:c7:9e:82:2e
Security Mode:	WPA2 Personal
Encryption Algorithm:	AUTO
Status:	Connected
Wi-Fi Direct:	Enabled
Wireless Hardware:	Installed
Wi-Fi Protected Setup™ (WPS) Name:	Xerox AltaLink B8255 MFP (19:DA:
Access Point (SSID):	DIRECT-ZQ-Xerox AltaLink B8255 M
Show Password on Device Touch Screen:	Enabled
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di..	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.11.61
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.11.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Enabled
Link Local Address:	fe80::5aef:68ff:fe27:6740
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	fd00:0:2:111:b5e2:50ec:4a0:dec4
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway:	fe80::80fc:5dff:fe75:e282
DUID (DHCP Unique Identifier):	
DNS Settings:	
Requested Host Name:	XXRXE84DEC19DA41
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati..	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled
Bonjour:	
Bonjour Printer Name:	Xerox AltaLink B8255 MFP (19:DA:41)
HTTP:	Enabled
Force Traffic over Secure Connection (H..	Yes
IPP	Enabled
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled
LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA..	Disabled
LDAP Server 1 Validate Server Certificate..	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0

Workflow Scanning:

Enabled:	Enabled
----------	---------

Email:

Enabled:	Enabled
----------	---------

Scan to Mailbox:

Enabled:	Enabled
----------	---------

Storage Capacity (MB):	46924 MB
------------------------	----------

Storage Used (MB):	2440 MB
--------------------	---------

Cleanup of Public Folders:	Enabled
----------------------------	---------

Cleanup of Created Folders:	Enabled
-----------------------------	---------

Cleanup Time:	Daily
---------------	-------

Scan to Home:

Disabled:	Disabled
-----------	----------

Scan To:

Enabled:	Enabled
----------	---------

Cloud Services:

Disabled:	Disabled
-----------	----------

Print From:

Enabled:	Enabled
----------	---------

Saved Jobs for Reprint:	Enabled
-------------------------	---------

Print From USB:	Enabled
-----------------	---------

Print From MailBox:	Disabled
---------------------	----------

Cloud Services:	Disabled
-----------------	----------

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Kerberos:	Disabled
-----------	----------

Xerox Secure Access:

Disabled:	Enabled
-----------	---------

Audit Log:

Enabled:	Disabled
----------	----------

IP Sec:

Disabled:	Disabled
-----------	----------

IP Filtering:

Disabled:	Disabled
-----------	----------

Security Certificates

Machine Certificate:	Signed
----------------------	--------

Root Certificates Installed:	48
------------------------------	----

802.1x:

Disabled:	Disabled
-----------	----------

Job Data Removal:

Disabled:	Disabled
-----------	----------

FIPS 140-3:

Disabled:	Disabled
-----------	----------

TLS:

TLS 1.2 and TLS 1.3:	
----------------------	--

TLS Hash:

SHA-1, SHA-256 and above:	
---------------------------	--

Trellix Embedded Control:

Enhanced Security:	
--------------------	--

Common User Data

Machine Name: Xerox AltaLink B8255 MFP (19:DA:41)
IPv4 Address: 10.61.11.61
Machine Serial Number: ZQV624012
Fax Line 1:
Machine URL: https://10.61.11.61
Machine Activation Date: Jan 01, 2021 05:45:36
Total Impressions: 314

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
Recycling Phone Number:
System Administrator:
Machine Location:
Managed By
Primary MB Server:

Machine Hardware

Fax Card: Not Present
Fax Memory Size: 0 MB
Foreign Interface Card: not present
Device RAM Size: 4096 MB
Device Storage Size: used=3320MB/total=256060MB (SSD)
EPC Memory Size: 900 MB
Finisher Type: Offsetting Catch Tray
Finisher Punch: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 21:04
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Metered
Billing Impression Mode: A3 Impressions
Geographic Region: unknown
Startup Config Report: Disabled
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Enabled
File Sharing: Enabled
JBIG2: Lossless

Energy Saver

Deep Sleep: Disabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled

Smart Proximity Sensor

Wake on Arrival: Enabled
Sleep on Departure: Disabled
Maximize Detection Range: Disabled

Software Versions

Device Software: 123.041.005.28800
Patch Version: None
Network Controller: 123.041.28800
UI Panel Firmware: 003.005.00000
User Interface: 123.041.28800
Marking Engine: 072.002.000
Copy Controller: 123.041.28800
Document Feeder: 023.026.000
Finisher: 000.000.000
Fax: 000.000.000
OS: 123.005.28710
Scanner: 017.025.003
Software Upgrade: 123.041.28800

Machine Upgrades

Last Successful Upgrade: October 22, 2025 16:26:09
Scheduled Auto Upgrades: Enabled
Auto Upgrade Start Time: Daily
Auto Upgrade Server: 10.61.9.116:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Tray 2: Plain, White and A3 (297 x 420 mm)
Tray 3: Plain, White and A4 (210 x 297 mm)
Tray 4: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled
Universal Print: Disabled
Universal Print Registration Status: Not Registered

Physical Connections

USB Settings

USB Type A Ports: All Enabled
USB Type B Port: Enabled
Connection Timeout: 5 seconds

Wired:

Ethernet MAC Address: e8:4d:ec:19:da:41
Ethernet Speed/Duplex Setting: auto

Wireless:

Wireless MAC Address: 58:ef:68:27:67:40
Network Name (SSID): Xerox Lab User
BSSID: bc:26:c7:9e:82:2e
Security Mode: WPA2 Personal
Encryption Algorithm: AUTO
Status: Connected

Wi-Fi Direct:

Wireless Hardware: Installed
Wi-Fi Protected Setup™ (WPS) Name: Xerox AltaLink B8255 MFP (19:DA:
Connection Method: Push Button Configuration (PBC)
Subnet Prefix Address: 172.26.65.0/24
Access Point (SSID): DIRECT-ZQ-Xerox AltaLink B8255 M
Show Password on Device Touch Screen: Enabled

NFC:

iBeacon (Bluetooth®) for AirPrint Di...
iBeacon Hardware: Enabled
Bluetooth Device Address: Enabled
iBeacon IP Address: Not Installed

Protocols

TCP/IPv4:

IPv4 Address: Enabled
10.61.11.61
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.11.1
Automatic Addressing: DHCP

DHCP Server:

DHCP Lease Expiration: Disabled
BOOTP Broadcast: Enabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
fe80::5aef:68ff:fe27:6740
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: ::
Stateless Global Address 2: ::
Manual Address: fd00:0:2:111:b5e2:50ec:4aa:dec4
DHCP Addressing: Use DHCP as directed by a router

DHCP Address:

Default Gateway: fe80::8afc:5dff:fe75:e282

DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRXE84DEC19DA41
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati... Disabled
Primary DNS Server: 10.61.7.16
Alternate DNS Server 1: 10.61.10.6
Alternate DNS Server 2: 10.61.7.15
DNS Connection Timeout: 5
Append Device Domain: Enabled
Append Parent Domains: Disabled
DNS Domain Search List: XEROXQA.COM.
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Apps

Bonjour:	
Bonjour Printer Name:	Xerox AltaLink B8255 MFP (19:DA:41)
HTTP:	
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Manual
Proxy Server Address:	10.177.8.91.8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.11.61.631
SNMP:	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	
Port Number:	515
FDL Switching:	Disabled
FDL Banner Override:	Disabled
Raw IP Printing:	
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
FDL Switching:	Disabled
LDAP:	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP:	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3:	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTF:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services:	
Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
ELP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
ELP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=210mm, y=297mm
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Main Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	Offset Between Jobs
PostScript:	
Level:	3
Version:	3021.101
Image Quality:	Standard
PCL:	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	64
Custom Color Tables:	Enabled
Label:	Not Installed

Fax:

Fax Line1:	Not Present
Fax Line2:	Not Present

Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	Errors Only
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	10.61.23.93:445
Default Repository Login Credentials:	/
Alt1 Repository Protocol:	Device
Alt1 Repository Server:	SMB
Alt1 Repository Document Path:	0.0.0.0
Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	SMB
Workflow Pool Server:	0.0.0.0
Workflow Pool Path:	

Email:

Default From Address:	Enabled
Confirmation Sheet:	Errors Only
Auto Send to Self:	Disabled
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	46924 MB
Storage Used (MB):	2440 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Friendly Name:	Disabled
Workflow Name:	Disabled
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
Print From:	
Saved Jobs for Reprint:	Disabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security**Authentication Configuration**

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm: Kerberos
Kerberos Primary Address: 0.0.0.88
Kerberos Alt 1 Realm: 0.0.0.88
Kerberos Alt 1 Address: 0.0.0.88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 48

802.1x:

Disabled

Job Data Removal:

Scheduled: Disabled
Scheduled Frequency:

FIPS 140-3:

Disabled

TLS

TLS 1.2 and TLS 1.3

TLS Hash:

SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_011_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123

